

Genius

ROBUSTNESS, RELIABILITY AND VERSATILITY

Floodlights in die-cast aluminium for halogen lamps
500/1000/1500 W.

Reflector in aluminium 99.85 polished and anodized. Tempered glass, silicone seals. Stainless steel nuts and bolts.

Protection from corrosion ensured by the polyester powder coating for outdoors in graphite grey finishing.

**HIGH LIGHT EMISSION, LESS ENCUMBRANCES
AND IMMEDIATE SWITCHING ON OF THE LIGHT**



GENIUS RANGE

MULTIFUNCTION FLOODLIGHTS FOR FIXED OR MOVABLE USE

GEWISS

CHARACTERISTICS AND ADVANTAGES

GENIUS RANGE



▶ HIGH RESISTANCE TO ATMOSPHERIC AGENTS

The thermosetting polyester powder and galvanized steel bracket painted in the same colour as the product, give not only high corrosion/resistance, but also a pleasant, high quality appearance.

▶ SIMPLIFIED MAINTENANCE AND REPLACEMENT

Front opening of the frame with retainer screws. The unlosable hexagonal screws made of stainless steel always ensure simplified maintenance over time.



▶ SHORTER INSTALLATION TIME

The external supply unit permits easy access to the terminal screw and terminal for cables up to 2.5 mm².



▶ STURDINESS

GENIUS is an extremely sturdy floodlight and is also suitable for portable building site applications.



▶ SWITCHES ON AUTOMATICALLY

Version with infrared sensors for switching on instantaneously and only when the user is present, adjustable from 10 to 300 seconds. The detector can be directed and also includes the photoelectric cell function (threshold 5-50 lux).

ACCESSORIES

The range of complementary items includes: spike, protective wire guard, lens hood and anti-glare louvre.