

Urano

NEWS
ATEX

IN PRAISE OF VERSATILITY

Floodlight for outdoors and indoors in die-cast aluminium, asymmetrical optics made in aluminium 99.85 polished and anodized.

Frame can be opened with hexagonal stainless steel screws hinged to the body. The seal is in silicone.

The bracket is painted the same colour as the floodlight and the finishings available - Aluminium, Graphite grey and White - are made with outdoor paints and powders so as to ensure a high degree of resistance to atmospheric agents.

AVAILABLE TODAY IN THE ATEX VERSION



URANO RANGE

COMPACT ASYMMETRICAL FLOODLIGHTS FOR OUTSIDE AND INSIDE

GEWISS

CHARACTERISTICS AND ADVANTAGES

URANO RANGE



ATEX VERSION



ATEX

The very latest range of URANO floodlights in conformity with directive 94/9/CE (ATEX).


The products are suited to all environments, indoors or outdoors, and are classified in accordance with the ATEX directive, ZONE 2 (GAS) and ZONE 22 (POWDER).

MAXIMUM PROTECTION AGAINST SUPERFICIAL ELECTRIC DISCHARGE

In order to avoid any superficial electrostatic discharge that could potentially be dangerous, an external earth connection is provided with the floodlight, as an extra to the standard one inside the wiring plate.

ALL METAL

Even the cable gland is made out of metal in order to guarantee maximum protection against the penetration of solid build-ups.



NON-SPARKING COMPONENTS

Special non-sparking electric components are used in order to guarantee the highest degrees of safety when using the product. No sparks will be able to trigger potentially explosive **gas** or **powders**, therefore guaranteeing absolute safety of the entire system.



URANO RANGE

COMPACT ASYMMETRICAL FLOODLIGHTS FOR OUTSIDE AND INSIDE

GEWISS

CHARACTERISTICS AND ADVANTAGES

STANDARD VERSION

URANO RANGE



◀ HIGH CORROSION RESISTANCE

The high degree of protection, the Alodine 1200 corrosion-proof treatment and the polyester powder painting ensure a resistance to corrosive agents and saline mist greater than what is provided for by the standard (EN 60068-2-52).


◀ ACCESSORIES

Protective wire guard to protect the glass from accidental jolts. It is easily integrated into the framework of the floodlight even if the product is already installed.



◀ SIMPLIFIED MAINTENANCE AND LAMP CHANGE

Front opening of the frame by rotation with retainer screw.



◀ EASY INSTALLATION AND MAINTENANCE

External stainless steel hexagonal screws to make assembly and maintenance operations simpler. All the screws are the unlosable type

▶ AIMING PRECISION AND SPEED

Thanks to the fixing bracket with graduated goniometric scale.



◀ HIGH RESISTANCE TO THERMAL SHOCKS AND PROTECTION FROM ACCIDENTAL KNOCKS

Tempered glass and protective wire guard available as complementary items.



◀ RANGE

URANO is available in three different colours: graphite grey, aluminium and white in order to afford optimum architectural integration to any installation environment.