

## GEWISS ACTIVO CONTROL UNITS WITH ELECTRONIC UNIT

### FULL



**FLUSH-MOUNTING CONTROL UNITS COMPLETE WITH RESIDUAL CURRENT CIRCUIT BREAKER, WITH BUILT-IN RESTART AND AUTOTEST FUNCTIONS AND ONE-WAY SWITCHES WITH ICU=4.5 KA - EQUIPPED WITH MONITORING UNIT FOR THE SYSTEM - 230V - 50/60HZ - IP40**

| Code                                   | In<br>RCCB | MCB<br>10 A | MCB<br>16 A | Enclosures<br>colour | Free<br>modules | Pack<br>Carton |
|--|------------|-------------|-------------|----------------------|-----------------|----------------|
| <b>No. EN 50022 MODULES: 12</b>        |            |             |             |                      |                 |                |
| GW 40 801                              | 25 A       | 1           | 3           | White                | 2               | 1/2            |
| GW 40 811                              | 25 A       | 1           | 3           | Titanium             | 2               | 1/2            |
| <b>No. EN 50022 MODULES: 24 (12x2)</b> |            |             |             |                      |                 |                |
| GW 40 821                              | 40 A       | 2           | 5           | White                | 11              | 1/2            |
| GW 40 831                              | 40 A       | 2           | 5           | Titanium             | 11              | 1/2            |

**NOTE:** the control units can also be completed with the "GEWISS BIOCOMFORT GW96339" circuit breaker for executions in the Bioarchitecture field.

**CHARACTERISTICS:** residual current circuit breaker type A, I<sub>dn</sub>=30 mA. miniature circuit breakers 2 poles, C curve, I<sub>cu</sub>=4.5 kA.

**COMPOSITION:** 1 SELF-TEST residual current circuit breaker with reset;

1 shunt trip release to associate with a circuit breaker for controlling a "non priority" load.

### EMPTY



GW40271

**FLUSH-MOUNTING ENCLOSURES WITH AUTOMATIC DOOR OPENING EQUIPPED WITH MONITORING UNIT FOR THE SYSTEM 230V - 50/60HZ - IP40**

| Code                                   | Colour            | External Dim.<br>LxHxD (mm) | Dispersable<br>power (W) | Pack<br>Carton |
|--|-------------------|-----------------------------|--------------------------|----------------|
| <b>No. EN 50022 MODULES: 12</b>        |                   |                             |                          |                |
| GW 40 251                              | Cloud white       | 320 x 255 x 80              | 26                       | 1/2            |
| GW 40 271                              | Metallic titanium | 320 x 255 x 80              | 26                       | 1/2            |
| <b>No. EN 50022 MODULES: 24 (12x2)</b> |                   |                             |                          |                |
| GW 40 256                              | Cloud white       | 320 x 360 x 80              | 36                       | 1/2            |
| GW 40 276                              | Metallic titanium | 320 x 360 x 80              | 36                       | 1/2            |

**NOTES:** dispersible power calculated according to CEI 23-49.

**ACCESSORIES SUPPLIED:** press-on labels with symbol for service identification. Cables complete with prods and supporting terminal block for connection of the intelligent unit. Sensors for measuring absorbed current and residual current. Module masks.

**APPLICATIONS:** domestic or similar environments with supply of up to 6KW. Full insulation to standard IEC 536.

## CO-ORDINATED SYMBOL ENCLOSURE

### FULL



**FLUSH-MOUNTING CONTROL UNITS COMPLETE WITH RESIDUAL CURRENT CIRCUIT BREAKER, WITH BUILT-IN RESTART AND AUTOTEST FUNCTIONS AND ONE-WAY SWITCHES WITH ICU=4.5 KA**

| Code                                   | In<br>RCCB | MCB<br>10 A | MCB<br>16 A | Enclosures<br>colour | Free<br>modules | Pack<br>Carton |
|--|------------|-------------|-------------|----------------------|-----------------|----------------|
| <b>No. EN 50022 MODULES: 12</b>        |            |             |             |                      |                 |                |
| GW 40 741                              | 25 A       | 1           | 2           | White                | 4               | 1/2            |
| GW 40 751                              | 25 A       | 1           | 2           | Titanium             | 4               | 1/2            |
| <b>No. EN 50022 MODULES: 24 (12x2)</b> |            |             |             |                      |                 |                |
| GW 40 761                              | 40 A       | 2           | 4           | White                | 13              | 1/2            |
| GW 40 771                              | 40 A       | 2           | 4           | Titanium             | 13              | 1/2            |

**NOTE:** the control units can also be completed with the "GEWISS BIOCOMFORT GW96339" circuit breaker for executions in the Bioarchitecture field.

**CHARACTERISTICS:** residual current circuit breaker type A, I<sub>dn</sub>=30 mA. Miniature circuit breakers 2 poles, C curve, I<sub>cu</sub>=4.5 kA.

**COMPOSITION:** 1 SELF-TEST residual current circuit breaker.

## EMPTY

GW40703



### ENCLOSURES CO-ORDINATED WITH PLAYBUS/SYSTEM/ECO60 RANGE PLATES - WITH SPACE FOR IDENTIFYING LABEL

H<sub>alogen</sub> F<sub>ree</sub>

| Code                                   | Colour            | External Dim.<br>LxHxD (mm) | Dispersable<br>power (W) | Characteristics | Pack<br>Carton |
|--|-------------------|-----------------------------|--------------------------|-----------------|----------------|
| <b>No. EN 50022 MODULES: 12</b>        |                   |                             |                          |                 |                |
| GW 40 701                              | Cloud white       | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 702                              | Toner black       | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 703                              | Geranium red      | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 704                              | Classic burgundy  | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 705                              | Venetian green    | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 706                              | Racing green      | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 707                              | Sky blue          | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 708                              | Jazz blue         | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 709                              | Corn yellow       | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 711                              | Metallic titanium | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 712                              | Metallic slate    | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 716                              | English walnut    | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 717                              | Soft chrome       | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| GW 40 718                              | Antique gold      | 320 x 255 x 80              | 26                       | Halogen free    | 1/2            |
| <b>No. EN 50022 MODULES: 24 (12x2)</b> |                   |                             |                          |                 |                |
| GW 40 721                              | Cloud white       | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 722                              | Toner black       | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 723                              | Geranium red      | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 724                              | Classic burgundy  | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 725                              | Venetian green    | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 726                              | Racing green      | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 727                              | Sky blue          | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 728                              | Jazz blue         | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 729                              | Corn yellow       | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 731                              | Metallic titanium | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 732                              | Metallic slate    | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 736                              | English walnut    | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 737                              | Soft chrome       | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |
| GW 40 738                              | Antique gold      | 320 x 360 x 80              | 36                       | Halogen free    | 1/2            |

**NOTES:** dispersible power calculated according to CEI 23-49.

**ACCESSORIES SUPPLIED:** module masks, service identification labels. Neutral indicator label.

## DECORATIVE ENCLOSURES

GW40237



### FLUSH-MOUNTING DECORATIVE ENCLOSURES WITH SMOKED TRANSPARENT DOOR FITTED TO HOUSE TERMINAL BLOCKS - IP40

| Code                                   | Colour      | External Dim.<br>LxHxD (mm) | Dispersable<br>power (W) | Installable<br>terminal blocks | Characteristics | Pack<br>Carton |
|--|-------------|-----------------------------|--------------------------|--------------------------------|-----------------|----------------|
| <b>No. EN 50022 MODULES: 4</b>         |             |                             |                          |                                |                 |                |
| GW 40 237                              | White       | 130 x 160 x 85              | 17                       |                                | Halogen free    | 12             |
| GW 40 238                              | Toner black | 130 x 160 x 85              | 17                       |                                | Halogen free    | 12             |
| <b>No. EN 50022 MODULES: 8</b>         |             |                             |                          |                                |                 |                |
| GW 40 225                              | White       | 230 x 185 x 72              | 17                       | GW40401                        | Halogen free    | 16             |
| GW 40 226                              | Toner black | 230 x 185 x 72              | 17                       | GW40401                        | Halogen free    | 16             |
| <b>No. EN 50022 MODULES: 12</b>        |             |                             |                          |                                |                 |                |
| GW 40 229                              | White       | 310 x 190 x 72              | 22                       | GW40402                        | Halogen free    | 12             |
| GW 40 230                              | Toner black | 310 x 190 x 72              | 22                       | GW40402                        | Halogen free    | 12             |
| <b>No. EN 50022 MODULES: 24 (12x2)</b> |             |                             |                          |                                |                 |                |
| GW 40 233                              | White       | 310 x 330 x 80              | 31                       | 2 x GW40401                    | Halogen free    | 5              |
| GW 40 234                              | Toner black | 310 x 330 x 80              | 31                       | 2 x GW40401                    | Halogen free    | 5              |
| <b>No. EN 50022 MODULES: 36 (12x3)</b> |             |                             |                          |                                |                 |                |
| GW 40 239                              | White       | 310 x 483 x 90              | 45                       | 2 x GW40402                    | Halogen free    | 5              |
| GW 40 240                              | Toner black | 310 x 483 x 90              | 45                       | 2 x GW40402                    | Halogen free    | 5              |

**NOTES:** dispersible power calculated according to CEI 23-49.

**ACCESSORIES SUPPLIED:** module masks, service identification labels. Neutral indicator label.