

SURFACE-MOUNTING ROTARY SWITCHES - IP65

CONTROL VERSION



GW70401

SURFACE-MOUNTING ROTARY CONTROL SWITCHES COMMAND VERSION WITH BLACK KNOB - IP65

Code	No. poles	External Dim. LxHxD (mm)	Pack Carton
RATED CURRENT (A): 16			
GW 70 401	2	114 x 114 x 71,5	1/16
GW 70 402	3	114 x 114 x 71,5	1/16
GW 70 403	4	114 x 114 x 71,5	1/16
RATED CURRENT (A): 32			
GW 70 404	2	114 x 114 x 71,5	1/16
GW 70 405	3	114 x 114 x 71,5	1/16
GW 70 406	4	114 x 114 x 71,5	1/16
RATED CURRENT (A): 63			
GW 70 407	3	170 x 170 x 96	1/6
GW 70 408	4	170 x 170 x 96	1/6

EMERGENCY VERSIONS



GW70432

ROTARY CONTROL SURFACE-MOUNTING EMERGENCY SWITCHES WITH RED PADLOCKABLE KNOB ON YELLOW FLANGE - IP65

Code	No. poles	External Dim. LxHxD (mm)	Pack Carton
RATED CURRENT (A): 16			
GW 70 431	2	114 x 114 x 71,5	1/16
GW 70 432	3	114 x 114 x 71,5	1/16
GW 70 433	4	114 x 114 x 71,5	1/16
RATED CURRENT (A): 32			
GW 70 434	2	114 x 114 x 71,5	1/16
GW 70 435	3	114 x 114 x 71,5	1/16
GW 70 436	4	114 x 114 x 71,5	1/16
RATED CURRENT (A): 63			
GW 70 437	3	170 x 170 x 96	1/6
GW 70 438	4	170 x 170 x 96	1/6

ACCESSORIES SUPPLIED: GW44622 screwcaps.

Complete insulation in compliance with standard IEC 536 which can be achieved with the use of GW44622 screwcaps or GW44621 fixing brackets.

ROTARY CONTROL SWITCHES FOR DISTRIBUTION BOARD

VERSION FOR DOOR LOCKING



GW70001

ROTARY CONTROL SWITCHES FOR DISTRIBUTION BOARD, VERSION FOR DOOR LOCKING WITH PADLOCKABLE RED KNOB AND CONTROL TRANSMISSION SHAFT

Code	No. poles	No. EN 50022 modules	Regulation field	Pack Carton
RATED CURRENT (A): 16				
GW 70 001	2	3	87 - 145 mm	1/10
GW 70 002	3	3	87 - 145 mm	1/10
GW 70 003	4	3	87 - 145 mm	1/10
RATED CURRENT (A): 32				
GW 70 004	2	4	87 - 145 mm	1/10
GW 70 005	3	4	87 - 145 mm	1/10
GW 70 006	4	4	87 - 145 mm	1/10
RATED CURRENT (A): 63				
GW 70 007	3	5	114 - 177 mm	1/5
GW 70 008	4	5	114 - 177 mm	1/5

CHARACTERISTICS: the regulation field can be obtained by cutting the shaft supplied. Correctly installed, it ensures the IP65 protection rating.

GW7009



GALVANIZED STEEL EXTENDING BRACKETS FOR REAR FIXING, COMPLETE WITH SELF-TAPPING SCREWS - SET OF 4 BRACKETS

Code	For rotary control switches	Regulation field	Pack Carton
GW 70 009	16A - 32A - 63A	117-305 mm (16/32A) 144-337 mm (63A)	1/10

CHARACTERISTICS: the regulation field can be obtained by cutting both the shaft supplied and the extension brackets at the references shown.

VERSION FOR FIXING ON RAIL DIN

GW7023



ROTARY CONTROL SWITCHES FOR DIN RAIL WITH BLACK HANDLE



Code	No. poles	No. EN 50022 modules	Pack Carton
RATED CURRENT (A): 16			
GW 70 201	2	3	1/30
GW 70 202	3	3	1/30
GW 70 203	4	3	1/30
RATED CURRENT (A): 32			
GW 70 204	2	4	1/24
GW 70 205	3	4	1/24
GW 70 206	4	4	1/24
RATED CURRENT (A): 63			
GW 70 207	3	5	1/12
GW 70 208	4	5	1/12

APPLICATIONS: the rotary control switches can be used for the following services according to the categories of use:

AC-22 (mixed, resistive and inductive load control with modest overloading),

AC-3 (cage motor operation on starting and in arrangement with motor running),

AC-23 (control of motors or other high induction loads) (CEI EN 60947-3 and CEI 17-11).

COMPLEMENTARY ITEMS

GW70410



PADLOCKABLE RED KNOBS WITH YELLOW FLANGE FOR EMERGENCY

Code	For rotary control switches	Pack Carton
GW 70 409	16A - 32A	1/20
GW 70 410	63A	1/18

APPLICATIONS: suitable for maintenance of control versions in the case one wants to make emergency versions.