





44 CEP - WATERTIGHT BOARDS IN GWPLAST 120 - GWT 650 °C - IP55



DISTRIBUTION BOARDS



WATERTIGHT BOARDS WITH BLANK DOOR FITTED WITH LOCK - GREY RAL 7035

H_{alogen} F_{ree}

| Code | External Dim. LxHxD (mm) | N. modules EN 50022 max | No. locks | Characteristics | Pack Carton |
|-----------|-----------------------------|----------------------------|-----------|-----------------|----------------|
| GW 44 808 | 200 x 254 x 135 | | 1 | Halogen free | 4 |
| GW 44 809 | 236 x 316 x 135 | 8 | 1 | Halogen free | 4 |
| GW 44 810 | 316 x 396 x 160 | 24 (12X2) | 2 | Halogen free | 2 |
| GW 44 811 | 396 x 474 x 160 | 32 (16X2) | 2 | Halogen free | 2 |

CHARACTERISTICS: doors equipped with functional grid of reference for fixing devices.

ACCESSORIES SUPPLIED: frame for semi-flush-mounting installations, screwcap for double insulation, triangular key.
GW44809, GW44810, GW44811 metal uprights for fixing of DIN rails.



WATERTIGHT BOARDS WITH TRANSPARENT DOOR FITTED WITH LOCK - GREY RAL 7035


H_{alogen} F_{ree}

| Code | External Dim. LxHxD (mm) | N. modules EN 50022 max | No. locks | Characteristics | Pack Carton |
|-----------|-----------------------------|----------------------------|-----------|-----------------|----------------|
| GW 44 818 | 200 x 254 x 135 | | 1 | Halogen Free | 4 |
| GW 44 819 | 236 x 316 x 135 | 8 | 1 | Halogen Free | 4 |
| GW 44 820 | 316 x 396 x 160 | 24 (12X2) | 2 | Halogen Free | 2 |
| GW 44 821 | 396 x 474 x 160 | 32 (16X2) | 2 | Halogen Free | 2 |

CHARACTERISTICS: doors equipped with functional grid of reference for fixing devices.

ACCESSORIES SUPPLIED: frame for semi-flush/mounting installations, screwcap for double insulation, triangular key.
GW44819, GW44820, GW44821, metal uprights for fixing of DIN rails.

INTERNAL CONFIGURATION



BACK-MOUNTING PLATE IN GALVANISED STEEL WITH SELF-TAPPING FIXING SCREWS

| Code | For dist. boards LxH (mm) | Pack Carton |
|-----------|------------------------------|----------------|
| GW 44 636 | 200 x 254 | 20 |
| GW 44 637 | 236 x 316 | 20 |
| GW 44 638 | 316 x 396 | 5 |
| GW 44 639 | 396 x 474 | 5 |



BACK-MOUNTING PLATE IN INSULATED MATERIAL WITH SELF-TAPPING FIXING SCREWS

| Code | For dist. boards LxH (mm) | Pack Carton |
|-----------|------------------------------|----------------|
| GW 44 646 | 200 x 254 | 20 |
| GW 44 647 | 236 x 316 | 20 |
| GW 44 648 | 316 x 396 | 4 |
| GW 44 649 | 396 x 474 | 5 |

CHARACTERISTICS: equipped with functional grid for fixing devices.

GW44854



PANELS WITH WINDOW FOR MODULAR DEVICES AND MOULDED-CASE CIRCUIT IN FIXED POSITION EXECUTION, UP TO 160 A COUPLING - GREY RAL 7035

| Code | No. EN 50022 modules | For dist.boards LxH (mm) | Suitable for | Disp. power flush-moun. (W) | Disp. power sur-mount. (W) | Characteristics | Pack Carton |
|-----------|----------------------|--------------------------|------------------------|-----------------------------|----------------------------|-----------------|-------------|
| GW 44 852 | 8 | 236 x 316 | Moulded case max 125 A | 21 | 17 | Halogen free | 1/8 |
| GW 44 853 | 14 | 316 x 396 | Moulded case max 160 A | 35 | 31 | Halogen free | 1/8 |
| GW 44 854 | 24 (12x2) | 316 x 396 | Moulded case max 125 A | 42 | 34 | Halogen free | 1/8 |
| GW 44 855 | 32 (16x2) | 396 x 474 | Moulded case max 160 A | 52 | 46 | Halogen free | 1/8 |

ACCESSORIES SUPPLIED: fixing uprights and DIN rails, module masks, service labels, self-adhesive label to be compiled for certification in compliance with standard CEI 23-51.

NOTE: Dispersible power calculated according to CEI 23-49, obtained by positioning the panels indicated in the relevant boards.

CHARACTERISTICS: halogen-free.

GW46451



SET OF 4 STEEL BRACKETS FOR FIXING BOARDS TO WALLS

| Code | Material | Accessories supplied | Pack Carton |
|-----------|------------------|----------------------|-------------|
| GW 46 446 | Galvanised steel | Fixing screws | 1/20 |
| GW 46 451 | Stainless steel | Fixing screws | 1/20 |

GW44621



WALL FIXING BRACKET

| Code | Material | Accessories supplied | For enclosures /dist.boards | Characteristics | Pack Carton |
|-----------|------------|----------------------------|-----------------------------|-----------------|-------------|
| GW 44 621 | Insulation | Fixing self-tapping screws | All wall types | Halogen Free | 40/480 |

GW46522



TRIANGULAR LOCK KIT

| Code | Description | Pack Carton |
|-----------|---------------------|-------------|
| GW 46 522 | Triangular key | 1/10 |
| GW 46 523 | Triangular lock kit | 1/10 |

GW46445



SAFETY LOCK WITH HANDLE

| Code | Description | Pack Carton |
|-----------|------------------------------------------|-------------|
| GW 46 445 | security lock safety lock key and handle | 1/10 |

ACCESSORIES SUPPLIED: 2 keys. All keys are supplied with standardised code.

46 RANGE


WATERTIGHT SURFACE-MOUNTING BOARDS FOR AUTOMATION AND DISTRIBUTION



46 RANGE

46 QP - WATERTIGHT BOARDS IN POLYESTER - IP65

INSTALLATION




20 J




EN 50085 (CEI 23-73)

IP65




EN 60529

GWT 960°C



EN 60695-2-11

TP >200°C



EN 60695-10-2

DISTRIBUTION BOARDS

WATERTIGHT BOARDS IN POLYESTER WITH BLANK DOOR FITTED WITH LOCK - GREY RAL 7035

GW46004



H_{alogen} F_{ree}

| Code | External Dim. LxHxD (mm) | No. EN 50022 modules | No. locks | Dispersable power (W) | Characteristics | Pack Carton |
|-----------|--------------------------|----------------------|-----------|-----------------------|-----------------|-------------|
| GW 46 001 | 250 x 300 x 160 | | 1 | 34 | Halogen Free | 1 |
| GW 46 002 | 310 x 425 x 160 | 36 (12x3) | 2 | 48 | Halogen Free | 1 |
| GW 46 003 | 405 x 500 x 200 | 54 (18x3) | 2 | 105 | Halogen Free | 1 |
| GW 46 004 | 405 x 650 x 200 | 72 (18x4) | 2 | 118 | Halogen Free | 1 |
| GW 46 005 | 515 x 650 x 250 | 96 (24x4) | 2 | 126 | Halogen Free | 1 |
| GW 46 006 | 585 x 800 x 300 | 140 (28x5) | 2 | 205 | Halogen Free | 1 |
| GW 46 007 | 800 x 1060 x 350 | 180 (36x5) | 2 | 337 | Halogen Free | 1 |

NOTE: dispersible power calculated according to CEI 23-49.

CHARACTERISTICS: doors equipped with functional grid of reference for fixing devices.

ACCESSORIES SUPPLIED: screwcaps for double insulation, 4 reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular equipment.

WATERTIGHT BOARDS IN POLYESTER WITH BLANK DOOR FITTED WITH TRANSPARENT WINDOW AND LOCK - GREY RAL 7035

GW46206



H_{alogen} F_{ree}

| Code | External Dim. LxHxD (mm) | No. EN 50022 modules | No. locks | Dispersable power (W) | Characteristics | Pack Carton |
|-----------|--------------------------|----------------------|-----------|-----------------------|-----------------|-------------|
| GW 46 201 | 250 x 300 x 160 | | 1 | 34 | Halogen Free | 1 |
| GW 46 202 | 310 x 425 x 160 | 36 (12x3) | 2 | 48 | Halogen Free | 1 |
| GW 46 203 | 405 x 500 x 200 | 54 (18x3) | 2 | 105 | Halogen Free | 1 |
| GW 46 204 | 405 x 650 x 200 | 72 (18x4) | 2 | 118 | Halogen Free | 1 |
| GW 46 205 | 515 x 650 x 250 | 96 (24x4) | 2 | 126 | Halogen Free | 1 |
| GW 46 206 | 585 x 800 x 300 | 140 (28x5) | 2 | 205 | Halogen Free | 1 |
| GW 46 207 | 800 x 1060 x 350 | 180 (36x5) | 2 | 337 | Halogen Free | 1 |

NOTE: dispersible power calculated according to CEI 23-49.

CHARACTERISTICS: for the transparent porthole version: GWT 650°C.

ACCESSORIES SUPPLIED: screwcaps for double insulation, 4 reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular equipment.

SPARE PARTS

GW46504



BLANK DOOR WITH LOCK

| Code | For dist. boards LxH (mm) | No. locks | Characteristics | Pack Carton |
|-----------|---------------------------|-----------|-----------------|-------------|
| GW 46 501 | 250x300 | 1 | Halogen free | 1/6 |
| GW 46 502 | 310x425 | 2 | Halogen free | 1/6 |
| GW 46 503 | 405x500 | 2 | Halogen free | 1/8 |
| GW 46 504 | 405x650 | 2 | Halogen free | 1/8 |
| GW 46 505 | 515x650 | 2 | Halogen free | 1/10 |
| GW 46 506 | 585x800 | 2 | Halogen free | 1/10 |
| GW 46 507 | 800x1060 | 2 | Halogen free | 1/10 |

TECHNICAL CHARACTERISTICS FROM PAGE 964

46 RANGE

WATERTIGHT SURFACE-MOUNTING BOARDS FOR AUTOMATION AND DISTRIBUTION



46 RANGE


GW46514



DOOR WITH TRANSPARENT WINDOW AND LOCK

| Code | For dist.boards LxH (mm) | No. locks | Characteristics | Pack Carton |
|-----------|-----------------------------|--------------|-----------------|----------------|
| GW 46 511 | 250x300 | 1 | Halogen free | 1/6 |
| GW 46 512 | 310x425 | 2 | Halogen free | 1/6 |
| GW 46 513 | 405x500 | 2 | Halogen free | 1/8 |
| GW 46 514 | 405x650 | 2 | Halogen free | 1/8 |
| GW 46 515 | 515x650 | 2 | Halogen free | 1/10 |
| GW 46 516 | 585x800 | 2 | Halogen free | 1/10 |
| GW 46 517 | 800x1060 | 2 | Halogen free | 1/10 |

46 QM - WATERTIGHT BOARDS IN METAL - IP55



DISTRIBUTION BOARDS

GW46034



WATERTIGHT BOARDS IN METAL WITH BLANK DOOR FITTED WITH LOCK - GREY RAL 7035

| Code | External Dim. LxHxD (mm) | No. EN 50022 modules | No. locks | Dispersable power (W) | Pack Carton |
|-----------|-----------------------------|-------------------------|--------------|--------------------------|----------------|
| GW 46 031 | 250 x 300 x 160 | | 1 | 49 | 1 |
| GW 46 032 | 310 x 425 x 160 | 36 (12x3) | 2 | 76 | 1 |
| GW 46 033 | 405 x 500 x 200 | 54 (18x3) | 2 | 106 | 1 |
| GW 46 034 | 405 x 650 x 200 | 72 (18x4) | 2 | 135 | 1 |
| GW 46 035 | 515 x 650 x 250 | 96 (24x4) | 2 | 228 | 1 |
| GW 46 036 | 585 x 800 x 300 | 140 (28x5) | 2 | 297 | 1 |
| GW 46 037 | 800 x 1060 x 350 | 180 (36x5) | 2 | 404 | 1 |

NOTE: dispersible power calculated according to CEI 23-49.

ACCESSORIES SUPPLIED: screwcaps, threaded pins or reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular equipment.

GW46034, GW46035, GW46036, GW46037 with perforated base equipped with flange for cables to pass through.

GW46232



WATERTIGHT BOARDS IN METAL WITH BLANK DOOR FITTED WITH TEMPERED

GLASS WINDOW AND LOCK - GREY RAL 7035



| Code | External Dim. LxHxD (mm) | No. EN 50022 modules | No. locks | Dispersable power (W) | Pack Carton |
|-----------|-----------------------------|-------------------------|--------------|--------------------------|----------------|
| GW 46 232 | 310 x 425 x 160 | 36 (12x3) | 2 | 76 | 1 |
| GW 46 233 | 405 x 500 x 200 | 54 (18x3) | 2 | 106 | 1 |
| GW 46 234 | 405 x 650 x 200 | 72 (18x4) | 2 | 135 | 1 |
| GW 46 235 | 515 x 650 x 250 | 96 (24x4) | 2 | 228 | 1 |
| GW 46 236 | 585 x 800 x 300 | 140 (28x5) | 2 | 297 | 1 |
| GW 46 237 | 800 x 1060 x 350 | 180 (36x5) | 2 | 404 | 1 |

NOTE: dispersible power calculated according to CEI 23-49.


ACCESSORIES SUPPLIED: screwcaps, threaded pins or reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular equipment.

GW46234, GW46235, GW46236, GW46237 with perforated base equipped with flange for cables to pass through.

46 QX - WATERTIGHT BOARDS IN STAINLESS STEEL - IP55



DISTRIBUTION BOARDS



WATERTIGHT BOARDS IN FINGERPRINT-PROOF SATIN STAINLESS STEEL WITH BLANK DOOR FITTED WITH LOCK

| Code | External Dim. LxHxD (mm) | No. EN 50022 modules | No. locks | Dispersable power (W) | Pack Carton |
|-----------|--------------------------|----------------------|-----------|-----------------------|-------------|
| GW 46 052 | 310 x 425 x 160 | 36 (12x3) | 2 | 76 | 1 |
| GW 46 054 | 405 x 650 x 200 | 72 (18x4) | 2 | 135 | 1 |
| GW 46 056 | 585 x 800 x 300 | 140 (28x5) | 2 | 297 | 1 |

APPLICATIONS: upon request, versions in stainless steel AISI 316 (particularly recommended for places with a high density of aggressive chemicals) are available.

NOTE: dispersible power calculated according to CEI 23-49.

ACCESSORIES SUPPLIED: screwcaps, threaded pins or reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular equipment.

GW46054, GW46056 with perforated base equipped with flange for cables to pass through.

COMPLEMENTARY ITEMS FOR 46 QP, QM AND QX BOARDS

FRONT CONFIGURATION




POLYESTER HINGED INNER DOORS TO MOUNT CONTROL, INDICATOR AND MEASURING DEVICES - GREY RAL

7035

| Code | For dist.boards LxH (mm) | Dist. second door et door | Characteristics | Pack Carton |
|-----------|--------------------------|---------------------------|-----------------|-------------|
| GW 46 414 | 310 x 425 | 32 mm | Halogen free | 1/5 |
| GW 46 415 | 405 x 500 | 32 mm | Halogen free | 1/4 |
| GW 46 416 | 405 x 650 | 32 mm | Halogen free | 1/5 |
| GW 46 417 | 515 x 650 | 32 mm | Halogen free | 1/2 |
| GW 46 418 | 585 x 800 | 32 mm | Halogen free | 1/2 |
| GW 46 419 | 800 x 1060 | 43 mm | Halogen free | 1 |

For further information about the distances between distribution board door, inner door and back-mounting plate, refer to the corresponding dimensional data.

CHARACTERISTICS: halogen-free.



PANELS WITH WINDOWS, 1 MODULE HIGH - GREY RAL 7035

| Code | No. EN 50022 modules | For dist.boards with dim mm | Characteristics | Pack Carton |
|-----------|----------------------|-----------------------------|-----------------|-------------|
| GW 46 420 | 12 | 310 | Halogen free | 1/10 |
| GW 46 421 | 18 | 405 | Halogen free | 1/10 |
| GW 46 422 | 24 | 515 | Halogen free | 1/10 |
| GW 46 423 | 28 | 585 | Halogen free | 1/5 |
| GW 46 424 | 36 | 800 | Halogen free | 1/5 |

ACCESSORIES SUPPLIED: fixing accessories. Complete with DIN rail.

CHARACTERISTICS: GW46420, GW46421, GW46422, GW46423, possibility of fixing directly onto the internal wall for the polyester distribution boards; halogen-free material.

NOTE: the GW46424 panel can be fixed only with GW46439 uprights in all distribution boards.



BLANK COVER PANELS - GREY RAL 7035

| Code | For boards B (mm) | Characteristics | Pack Carton |
|-------------------------|-------------------|-----------------|-------------|
| HEIGHT: 1 MODULE | | | |
| GW 46 425 | 310 | Halogen free | 1/10 |
| GW 46 426 | 405 | Halogen free | 1/10 |
| GW 46 427 | 515 | Halogen free | 1/13 |
| GW 46 428 | 585 | Halogen free | 1/5 |
| GW 46 429 | 800 | Halogen free | 1/5 |

TO BE CONTINUED ON NEXT PAGE

(TO BE CONTINUED)

BLANK COVER PANELS - GREY RAL 7035

| Code | For boards B (mm) | Characteristics | Pack Carton |
|--------------------------|----------------------|-----------------|----------------|
| HEIGHT: 2 MODULES | | | |
| GW 46 475 | 310 | Halogen free | 1/5 |
| GW 46 476 | 405 | Halogen free | 1/5 |
| GW 46 477 | 515 | Halogen free | 1/5 |
| GW 46 478 | 585 | Halogen free | 1/5 |
| GW 46 479 | 800 | Halogen free | 1 |

ACCESSORIES SUPPLIED: fixing accessories.

CHARACTERISTICS: GW46425, GW46426, GW46427, GW46428, GW46475, GW46476, GW46477, GW46478 possibility of directly fixing on the inside wall for the polyester distribution boards; halogen-free material. The GW46429 and GW46479 panels are fixed only with uprights GW46439 in all distribution boards.

GW46436



2 UPRIGHTS FOR THE INSTALLATION OF COMPLEMENTARY ITEMS FOR MODULAR DEVICES

| Code | For dist. boards LxH (mm) | Pack Carton |
|-----------|------------------------------|----------------|
| GW 46 435 | 310 x 425 | 1/10 |
| GW 46 436 | 405 x 500 | 1/10 |
| GW 46 437 | 405 x 650 / 515 x 650 | 1/10 |
| GW 46 438 | 585 x 800 | 1/10 |
| GW 46 439 | 800 x 1060 | 1/10 |

APPLICATIONS: allow you to create extractable frames, using covering panels and/or DIN rails and back-mounting plates.

GW46431



DIN RAILS

| Code | No. EN 50022 modules | For dist. boards with dim mm | Pack Carton |
|-----------|-------------------------|---------------------------------|----------------|
| GW 46 430 | 12 | 310 | 1/10 |
| GW 46 431 | 18 | 405 | 1/10 |
| GW 46 432 | 24 | 515 | 1/10 |
| GW 46 433 | 28 | 585 | 1/10 |
| GW 46 434 | 36 | 800 | 1/10 |

ACCESSORIES SUPPLIED: fixing accessories.

CHARACTERISTICS: fixing via uprights.

INTERNAL CONFIGURATION

GW46401



STEEL BACK-MOUNTING PLATES WITH ANTI-CORROSION TREATMENT FOR THE ASSEMBLY OF NON-MODULAR EQUIPMENT

| Code | For dist. boards LxH (mm) | Pack Carton |
|-----------|------------------------------|----------------|
| GW 46 401 | 250 x 300 | 1/5 |
| GW 46 402 | 310 x 425 | 1/5 |
| GW 46 403 | 405 x 500 | 1/5 |
| GW 46 404 | 405 x 650 | 1/5 |
| GW 46 405 | 515 x 650 | 1/4 |
| GW 46 406 | 585 x 800 | 1/3 |
| GW 46 407 | 800 x 1060 | 1 |

GW46464



PERFORATED BACK-MOUNTING PLATES IN GALVANISED STEEL FOR THE ASSEMBLY OF NON-MODULAR EQUIPMENT

| Code | For dist. boards LxH (mm) | Pack Carton |
|-----------|------------------------------|----------------|
| GW 46 461 | 250 x 300 | 1/5 |
| GW 46 462 | 310 x 425 | 1/5 |
| GW 46 463 | 405 x 500 | 1/5 |
| GW 46 464 | 405 x 650 | 1/5 |
| GW 46 465 | 515 x 650 | 1/4 |
| GW 46 466 | 585 x 800 | 1/3 |
| GW 46 467 | 800 x 1060 | 1/2 |

NOTES: use nut and clips GW46450 to install components.

GW46408



BACK-MOUNTING PLATES IN INSULATING MATERIAL FOR THE ASSEMBLY OF NON-MODULAR EQUIPMENT


| Code | For dist. boards LxH (mm) | Pack Carton |
|-----------|------------------------------|----------------|
| GW 46 408 | 250 x 300 | 1/5 |
| GW 46 409 | 310 x 425 | 1/5 |
| GW 46 410 | 405 x 500 | 1/5 |
| GW 46 411 | 405 x 650 | 1/4 |

TO BE CONTINUED ON NEXT PAGE

(TO BE CONTINUED)

BACK-MOUNTING PLATES IN INSULATING MATERIAL FOR THE ASSEMBLY OF NON-MODULAR EQUIPMENT

| Code | For dist.boards LxH (mm) | Pack Carton |
|-----------|-----------------------------|----------------|
| GW 46 412 | 515 x 650 | 1/3 |
| GW 46 413 | 585 x 800 | 1/2 |




GW46440

PERFORATED PLATES IN GALVANISED STEEL - FIXING VIA UPRIGHTS

| Code | For dist.boards LxH (mm) | No. EN 50022 modules | Pack Carton |
|--------------------------|-----------------------------|-------------------------|----------------|
| HEIGHT: 1 MODULE | | | |
| GW 46 440 | 310 x 425 | 12 | 1/5 |
| GW 46 441 | 405 x 500 / 405 x 650 | 18 | 1/5 |
| GW 46 442 | 515 x 650 | 24 | 1/5 |
| GW 46 443 | 585 x 800 | 28 | 1/5 |
| GW 46 444 | 800 x 1060 | 36 | 1/4 |
| HEIGHT: 2 MODULES | | | |
| GW 46 480 | 310 x 425 | 12 | 1/5 |
| GW 46 481 | 405 x 500 / 405 x 650 | 18 | 1/5 |
| GW 46 482 | 515 x 650 | 24 | 1/5 |
| GW 46 483 | 585 x 800 | 28 | 1/5 |
| GW 46 484 | 800 x 1060 | 36 | 1/2 |

NOTES: Use nut and clips GW46450 to install components



GW46450

NUT AND CLIPS IN GALVANISED STEEL FOR THE FIXING OF DEVICES ON TO PERFORATED BACK-MOUNTING PLATES

| Code | Description | Pack Carton |
|-----------|---------------------------|----------------|
| GW 46 450 | Clip nut for screw Ø 5 mm | 10/100 |


SERVICE COMPLEMENTARY ITEMS



GW46446
GW46451

SET OF 4 STEEL BRACKETS FOR FIXING BOARDS TO WALLS

| Code | Material | Accessories supplied | Pack Carton |
|-----------|------------------|----------------------|----------------|
| GW 46 446 | Galvanised steel | Fixing screws | 1/20 |
| GW 46 451 | Stainless steel | Fixing screws | 1/20 |



GW47291

MODULE MASK PROFILE IN PLASTIC MATERIAL - COLOUR GREY RAL 7035

| Code | No. EN 50022 modules | Pack Carton |
|-----------|-------------------------|----------------|
| GW 47 291 | 24 | 10 |

CHARACTERISTICS: clip fixing on DIN drilled front panels.



GW46449

SEAL FOR COUPLING BOARDS EQUIPPED WITH DRILLING TEMPLATE

| Code | Dimension (mm) | Pack Carton |
|-----------|-------------------|----------------|
| GW 46 449 | 295x150 | 1/10 |

APPLICATIONS: can be used on enclosures starting with the 405x500x200 size.

GW47196



AEROSOL SPRAY FOR RETOUCHING

| Code | Colour | Pack Carton |
|-----------|---------------|----------------|
| GW 47 196 | Grey RAL 7035 | 1/6 |

GW46521



SET OF 4 REVERSIBLE SQUARES TO SECURE BACK-MOUNTING PLATES OR UPRIGHTS FOR MODULAR EQUIPMENT

| Code | Description | Pack Carton |
|-----------|--------------------|----------------|
| GW 46 521 | Reversible squares | 1/20 |

ACCESSORIES SUPPLIED: fixing screws and bolts.

APPLICATIONS: permits combined installation of back-mounting plate and frame.

GW46522



TRIANGULAR LOCK KIT

| Code | Description | Pack Carton |
|-----------|---------------------|----------------|
| GW 46 522 | Triangular key | 1/10 |
| GW 46 523 | Triangular lock kit | 1/10 |

GW46445



SAFETY LOCK WITH HANDLE

| Code | Description | Pack Carton |
|-----------|------------------------------------------|----------------|
| GW 46 445 | security lock safety lock key and handle | 1/10 |

ACCESSORIES SUPPLIED: 2 keys. All keys are supplied with standardised code.

APPLICATIONS: for 46 QP, QX, QM and CEP boards.

GW46448



UNIVERSAL KIT FOR THE FORCED VENTILATION OF BOARDS - IP44 - 230 V - 50/60 HZ

| Code | Description | Fixing hole (mm) | Screws centre distances | Pack Carton |
|-----------|-----------------|---------------------|----------------------------|----------------|
| GW 46 448 | Ventilation kit | 125x117 | 123x115 | 1/2 |
| GW 46 471 | Aeration kit | 125x117 | 123x115 | 1/10 |

ACCESSORIES SUPPLIED: drilling template.

APPLICATIONS: forced ventilation in critical thermal conditions.

CHARACTERISTICS: the fan draws air from the outside and blows it into the distribution board, creating a slight increase in pressure that prevents foreign bodies from entering. Max. fan capacity equal to 60 m3/h.

GW46447



DOCUMENT HOLDER POCKET IN SELF-ADHESIVE INSULATING MATERIAL WITH KIT OF BLANK LABELS

| Code | Dimension (mm) | Pack Carton |
|-----------|-------------------|----------------|
| GW 46 447 | 310x230 | 1/10 |

CHARACTERISTICS: can be inserted in all Gewiss enclosures from dimension 405x500x200 mm upwards.

GW44651



SINGLE-POLE MODULAR DIVIDING TERMINAL BLOCK FIXING ON PLATE OR ON DIN RAIL - IP20

| Code | External Dim. LxHxD (mm) | No. EN 50022 modules | Input connecting capacity | Output connecting capacity | Pack Carton |
|-------------------------------|-----------------------------|-------------------------|------------------------------|-------------------------------|----------------|
| RATED CURRENT (A): 160 | | | | | |
| GW 44 651 | 35x92x49 | 2 | 1x10-70 mm ² | 6x2,5-16 mm ² | 1/5 |

CHARACTERISTICS: possibility of making single-, two-, three- and four-pole dividers. Terminal grip torque: cables entering 4Nm, cables exiting 1.5 Nm.

46 RANGE

WATERTIGHT SURFACE-MOUNTING BOARDS FOR AUTOMATION AND DISTRIBUTION

GEWISS

46 RANGE

GW44700



HORIZONTAL FOUR-POLE DIVIDER 250 A WITH PRE-DRILLED THREADED M6 BARS - 20X5 MM

| Code | Dimension (mm) | No. EN 50022 modules | Installation | Input connecting capacity | Output connecting capacity | Pack Carton |
|-----------|----------------|----------------------|---------------------|---------------------------|----------------------------|-------------|
| GW 44 700 | 285x190x70 | 16 | On profile EN 50022 | 1xM12 | 10xM6 | 1 |

ACCESSORIES SUPPLIED: installation clip on DIN rail.

TECHNICAL CHARACTERISTICS FROM PAGE 964