


## 42 RV - WATERTIGHT ENCLOSURES FOR EMERGENCY MANOEUVRES - IP55


### INSTALLATION



### IP55




### GWT 650°C



### TP 70°C



### CLASS II



EN 61140

## EQUIPMENT WITH ILLUMINABLE PUSH-BUTTON



GW42201

**WATERTIGHT ENCLOSURE FOR EMERGENCY SYSTEMS EQUIPPED WITH ILLUMINABLE PUSH-BUTTON FOR LOCATION AND TWO CONTACTS 1NO+1NC. ITH 10 A 240V**  
**PROVISION FOR USING GREEN LED EMERGENCY CIRCUIT INTEGRITY INDICATOR**

Code	External Dim. LxHxD (mm)	Colour	Pack Carton
GW 42 201	120 x 120 x 50	Red RAL 3000	1/10

**ACCESSORIES SUPPLIED:** substitute button key to enable configuration of manual or automatic action upon the breaking of the glass, self-adhesive pictograms "Break the glass" and "Press the button", screwcaps for double insulation, screws and accessories for the sealing of the frontal. Breakable glass "Sicur Push".

**CHARACTERISTICS:** possibility of mounting on flush-mounting box GW24203. Contact-holder flange with 2 seats.

**NOTE:** substitute contacts N/O: GW74201, N/C: GW74202; lamps for locating push-button: GW30941 12V~/, GW30942 24V~/, GW30943 230V~/; green LEDs for indicating emergency circuit integrity: GW30958 from 12 to 24V~/, GW30959 from 110 to 230V~/, GW30960 from 48V~/.

## FITTED WITH HOLE Ø 22 MM



GW42204

**WATERTIGHT ENCLOSURE FOR EMERGENCY SYSTEMS FITTED WITH HOLE Ø 22MM**

H<sub>alogen</sub> F<sub>ree</sub>

Code	External Dim. LxHxD (mm)	Colour	Characteristics	Pack Carton
GW 42 204	108 x 180 x 100	Red RAL 3000	Halogen free	1/10

**ACCESSORIES SUPPLIED:** Door fitted with lock with 2 keys, self adhesive pictogram "Break glass" and screwcaps for double insulation. "Sicur Push" breakable glass.

## WITH DIN RAIL



GW42202

**WATERTIGHT ENCLOSURES FOR EMERGENCY USE AND SPECIAL APPLICATIONS WITH RAIL DIN**

H<sub>alogen</sub> F<sub>ree</sub>

Code	No. EN 50022 modules	External Dim. LxHxD (mm)	Dispersable power (W)	Characteristics	Pack Carton
<b>COLOUR: RED RAL 3000</b>					
GW 42 206	4	108 x 180 x 100	12	Halogen free	1/10
GW 42 202	8	180 x 180 x 100	18	Halogen free	1/10
<b>COLOUR: GREY RAL 7035</b>					
GW 42 207	4	108 x 180 x 100	12	Halogen free	1/10
GW 42 208	8	180 x 180 x 100	18	Halogen free	1/10

**NOTES:** dispersible power calculated according to CEI 23-49.

**ACCESSORIES SUPPLIED:** Door fitted with lock with 2 keys, self adhesive pictogram « Break glass », service label and screwcaps for double insulation. Sicur Push breakable glass.

## WITH BACK-MOUNTING PLATE



GW42203

### WATERTIGHT ENCLOSURE FOR EMERGENCY USE AND SPECIAL APPLICATIONS WITH GALVANISED METAL BACK MOUNTING PLATE

H<sub>alogen</sub> F<sub>ree</sub>

Code	External Dim. LxHxD (mm)	Colour	Characteristics	Pack Carton
GW 42 203	180 x 180 x 100	Red RAL 3000	Halogen free	1/10

**ACCESSORIES SUPPLIED:** Door fitted with lock with 2 keys, self adhesive pictogram "Break glass" and screwcaps for double insulation. Full insulation, in compliance with standard EN 60439-1, can be achieved using screwcaps or GW44621 resin fixing brackets. "Sicur Push" breakable glass.

## FLUSH-MOUNTING ENCLOSURE WITH DIN RAIL



GW42232

### WATERTIGHT FLUSH-MOUNTING ENCLOSURES FOR EMERGENCIES AND SPECIAL APPLICATIONS WITH RAIL DIN

H<sub>alogen</sub> F<sub>ree</sub>

Code	No. EN 50022 modules	External Dim. LxHxD (mm)	Dispersable power (W)	Colour	Characteristics	Pack Carton
GW 42 231	4	145 x 200 x 70	12	Red RAL 3000	Halogen free	1/10
GW 42 232	4	145 x 200 x 70	12	Grey RAL 7035	Halogen free	1/10

**ACCESSORIES SUPPLIED:** Door fitted with lock with 1 key, self adhesive pictogram "Break glass" and service labels. Sicur Push breakable glass.

**NOTES:** should the flush-mounting box not be completely mounted to the wall, use the GW48645 screws spacers kit. Dispersible power calculated according to CEI 23-49.

## PLATES FOR LIFT / EMERGENCY - PLAYBUS RANGE

### WIRED PLATES FOR LIFT AND EMERGENCY



GW32450

#### SELF-SUPPORTING WIRED PLATES FOR LIFT/EMERGENCY WITH ILLUMINABLE BUTTON SWITCH, TRIANGLE KEY AND BREAKABLE GLASS - IP40

Code	Contacts	Colour	Suitable for	Pack Carton
GW 32 450	1 NO + 1 NC 10A (AC1) / 6A (AC15)	White	Lift	1/10
GW 32 451	1 NO + 1 NC	Red	Emergency	1/10

The articles are supplied with an 11mm button key already assembled, without a lamp. They use the following signalling units: GW30941 12V/-/, GW30942 24V/-/, GW30943 230V/-/.

**CHARACTERISTICS:** the plates are ready for a security lock GW40422, available as an accessory.

**ACCESSORIES SUPPLIED:** accessory button key, 17mm high, to operate the contacts when glass is broken.

### PLATES FITTED FOR PLAYBUS RANGE DEVICES



GW32452

#### SELF-SUPPORTING UNWIRED PLATES FOR EMERGENCY WITH TRIANGLE KEY AND BREAKABLE GLASS FITTED FOR MOUNTING MODULAR PLAYBUS DEVICES - IP40

Code	Colour	No. Playbus modules	Pack Carton
GW 32 452	White	2	1/10
GW 32 453	Red	2	1/10

**CHARACTERISTICS:** plates are fitted with GW40422 lock, available as accessory.

For flush-mounting enclosure GW24203, GW24204, GW24303; for surface mounting boxes GW32431, GW32432.

## COMPLEMENTARY ITEMS

### GLASS BREAKER




GW42216

#### GLASS BREAKER WITH UNIVERSAL FIXING SUPPORT

Code	Colour	Support dimension (mm)	Pack Carton
GW 42 216	Toner black	70 x 60	1/10

**CHARACTERISTICS:** the hammer is joined to the base with a fine chain, so it can not be lost.


### SPARE GLASS



GW32457

#### SPARE BREAKABLE GLASS

Code	For plates	Pack Carton
GW 32 457	GW32450 GW32451 GW32452 GW32453	1/10



GW42212

#### SPARE SICUR PUSH GLASS FOR WATERTIGHT ENCLOSURES FOR EMERGENCIES

Code	For enclosures	Pack Carton
GW 42 211	GW42201	1/10
GW 42 213	GW42204 GW42206 GW42207	1/10
GW 42 212	GW42202 GW42203 GW42208	1/10
GW 42 214	GW42231 GW42232	1/10


### ACCESSORIES AND SPARE PARTS



GW30941

#### MINIATURE LAMP

Code	Lamp voltage	Lamp power	Lamp type	Light emitted	Pack Carton
GW 30 941	12 V ac/dc	0.4 W	Incandescent	White	50
GW 30 942	24 V ac/dc	0.8 W	Incandescent	White	50
GW 30 943	230 V ac/dc	0.4 W	Fluorescent	Red	50
GW 30 945	110 V ac/dc	0.8 W	Fluorescent	White	50
GW 30 958	12-24 V ac/dc		Led	Green	10
GW 30 959	110-230 V ac/dc		Led	Green	10
GW 30 960	48 V ac/dc		Led	Green	1/10



GW74201

#### CONTACTS - ITH 10A - 240V~

Code	Type	Category of use 240 V AC15	Category of use 240 V DC13	Colour	Pack Carton
GW 74 201	1 NO	3 A	0,27 A	Green	10/60
GW 74 202	1 NC	3 A	0,27 A	Red	10/60

**CHARACTERISTICS:** GW74202, suitable for opening the contact also in the event of it slightly sticking, in conformity with the EN 60947-5-1 standard.

Mounting on the contact flanges snaps into place. Contacts compatible with emergency control unit GW42201.



GW48644

#### WATERTIGHT CYLINDRICAL SECURITY LOCK

Code	For enclosures	Material	Pack Carton
GW 48 644	48 PTC and 42 RV range	Pressure die-cast	1/10

**ACCESSORIES SUPPLIED:** 2 keys. All keys are supplied with standardised code.

# 42 RV RANGE

WATERTIGHT SURFACE AND FLUSH-MOUNTING EMERGENCY ENCLOSURES



GW40422



## CYLINDER SECURITY LOCK

Code	Suitable for	Pack Carton
GW 40 422	Playbus range of plates	1/10

**ACCESSORIES SUPPLIED:** 2 keys. All keys are supplied with standardised code.

GW48645



## KIT OF 4 LONG SELF-TAPPING SCREWS WITH SPACERS TO SECURE LIDS AND FRONTS

Code	Screw dimension (mm)	Spacer thickness (mm)	Pack Carton
GW 48 645	∅ 4x45	max 10 mm reducible	1/100

**CHARACTERISTICS:** the kit can also be used for the following flush-mounting ranges: CD/CDK (starting from 6 modules), 48 CM and 42 RV.

GW44621



## WALL FIXING BRACKET, COMPLETE WITH SELF-TAPPING SCREWS

Code	Suitable for	Characteristics	Pack Carton
GW 44 621	Enclosures 42 RV wall range	Halogen Free	40/480

**APPLICATIONS:** allow you to maintain the double insulation.

42 RV RANGE