



DISTRIBUTION TOWER AND BOARDS

INSTALLATION



GWT 650°C



TP 70°C



CLASS II



SURFACE-MOUNTING DISTRIBUTION BOARDS - IP41




SURFACE-MOUNTING ADAPTABLE BOARDS WITH REVERSIBLE DOOR WITH SMOOTH AND HONEYCOMBED SURFACE - COLOUR GREY RAL 7035

H_{alogen} F_{ree}

Code	External Dim. LxHxD (mm)	No. input	Characteristics	Pack Carton
GW 42 001	200 x 150 x 40	Ø 20,5 = 16	Halogen free	32
GW 42 002	200 x 150 x 60	Ø 20,5 = 12 Ø 20,5/23 = 4	Halogen free	44
GW 42 003	200 x 150 x 80	Ø 20,5 = 12 Ø 20,5/23 = 4	Halogen free	32
GW 42 004	300 x 200 x 40	Ø 20,5 = 16	Halogen free	16
GW 42 005	300 x 200 x 60	Ø 23/29 = 16	Halogen free	21
GW 42 006	300 x 200 x 80	Ø 23/29 = 16	Halogen free	16
GW 42 007	300 x 200 x 120	Ø 23/29 = 16	Halogen free	10
GW 42 008	400 x 300 x 60	Ø 23/29 = 22	Halogen free	10
GW 42 009	400 x 300 x 80	Ø 23/29 = 22	Halogen free	8
GW 42 010	400 x 300 x 120	Ø 23/29 = 22	Halogen free	5

FLOOR MOUNTING AND WORKBENCH TOWER - IP55



PILLAR WITH REVERSIBLE DOOR WITH SMOOTH AND HONEYCOMBED SURFACE COLOUR GREY RAL 7035

H_{alogen} F_{ree}

Code	External Dim. LxHxD (mm)	Houseable socket-o. IB type	Mountable Q-DIN	Characteristics	Pack Carton
GW 68 441	295 x 200 x 180	Compact 16A/32A	Q-DIN4	Halogen free	1/6

CHARACTERISTICS: opposing flanges with smooth and honeycomb surface to secure interlocked socket-outlets in the 66/67 IB range: Cambibloc, horizontal back-mounting socket-outlets, vertical SBF socket-outlets with back.

COMPLEMENTARY ITEMS



WATERPROOF COUPLER

Code	For holes mounting Ø (mm)	For mounting PG holes	Pack Carton
GW 26 406	23	16	25/250



BACK-MOUNTING PLATE WITH SELF-TAPPING FIXING SCREWS

Code	For boxes LxH dim. (mm)	For distribution boards	Pack Carton
MATERIAL: GALVANIZED METAL			
GW 44 615	190 x 140	GW42001 - GW42002 - GW42003	20
GW 44 616	240 x 190	GW42004 - GW42005 - GW42006 - GW42007	20
GW 44 617	300 x 220	GW42008 - GW42009 - GW42010	20
MATERIAL: INSULATION			
GW 44 625	190 x 140	GW42001 - GW42002 - GW42003	20
GW 44 626	240 x 190	GW42004 - GW42005 - GW42006 - GW42007	20
GW 44 627	300 x 220	GW42008 - GW42009 - GW42010	20

GW52402



CUP DRILL MILLING CUTTER TO DRILL PANELS

Code	Description	Pack Carton
GW 52 402	Cup drill milling Ø56	10

APPLICATIONS: suitable for low voltage flush-mounting socket-outlets IEC 309 2P+E 16A and for all the extra-low voltage flush-mounting socket-outlets IEC 309.