



MULTIFUNCTIONAL DEVICES



STANDARD

WIRED VERSIONS WITH P.F. CORRECTION COMPLETE WITH LAMP - IP55 - CLASS I




GW82281S



Code	Lamp power	Lamp supplied	Lamp holder	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 230 V - 50 Hz						
GW 82 281 S	70 W	SE*	E27	Graphite grey	3.4	1/2
GW 82 214 S	70 W	SE*	E27	White	3.4	1/2
GW 82 282 M	100 W	ME	E27	Graphite grey	3.4	1/2
GW 82 216 M	100 W	ME	E27	White	3.4	1/2
GW 82 283 Q	80 W	QE	E27	Graphite grey	2.9	1/2
GW 82 218 Q	80 W	QE	E27	White	2.9	1/2
VOLTAGE: 240 V - 50 Hz						
GW 82 275 S	70 W	SE*	E27	Graphite grey	3.4	1/2
GW 82 224 S	70 W	SE*	E27	White	3.4	1/2
GW 82 276 M	100 W	ME	E27	Graphite grey	3.4	1/2
GW 82 226 M	100 W	ME	E27	White	3.4	1/2
GW 82 277 Q	80 W	QE	E27	Graphite grey	2.9	1/2
GW 82 228 Q	80 W	QE	E27	White	2.9	1/2
VOLTAGE: 220 V - 60 Hz						
GW 82 278 S	70 W	SE*	E27	Graphite grey	3.4	1/2
GW 82 234 S	70 W	SE*	E27	White	3.4	1/2
GW 82 279 M	100 W	ME	E27	Graphite grey	3.4	1/2
GW 82 236 M	100 W	ME	E27	White	3.4	1/2
GW 82 280 Q	80 W	QE	E27	Graphite grey	2.9	1/2
GW 82 238 Q	80 W	QE	E27	White	2.9	1/2

* Use lamps with built-in ignitor.

WIRED VERSIONS WITH P.F. CORRECTION- IP55 - CLASS I



GW82284



Code	No. lamps	Lamp power	Lamp type	Lamp holder	Power supply	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 230 V - 50 Hz								
GW 82 284	2	18 W	FSD	2G11	Standard	Graphite grey	2.3	1/2
GW 82 212	2	18 W	FSD	2G11	Standard	White	2.4	1/2
VOLTAGE: 240 V - 50 Hz								
GW 82 287	2	18 W	FSD	2G11	Standard	Graphite grey	2.3	1/2
GW 82 222	2	18 W	FSD	2G11	Standard	White	2.4	1/2
VOLTAGE: 220 V - 60 Hz								
GW 82 288	2	18 W	FSD	2G11	Standard	Graphite grey	2.3	1/2
GW 82 232	2	18 W	FSD	2G11	Standard	White	2.4	1/2

NEW

VERSIONS FOR INCANDESCENT LAMPS

GW82206



Code	Max. lamp power	Lamp type	Lamp holder	Colour	Weight (Kg)	Pack Carton
GW 82 206	100 W	IA / IB - HS - FTB	E27	Graphite grey	1.9	1/2
GW 82 202	100 W	IA / IB - HS - FTB	E27	White	1.9	1/2

ACCESSORIES SUPPLIED: structural components: reflector, accessory-holding plate. Electrical components: lampholder with cables, supply terminal.
Devices are supplied with standard service items.

ELECTRONIC BALLAST

WIRED VERSIONS WITH P.F. CORRECTION- IP55 - CLASS I

GW82286



Code	No. lamps	Lamp power	Lamp type	Lamp holder	Power supply	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 220 / 240 V - 50 / 60 Hz								
GW 82 286	2	26 W 32 W	FSQ	GX24q-3	Electronic	Graphite grey	2.1	1/2
GW 82 242	2	26 - 32 W	FSQ	GX24q-3	Electronic	White	2.1	1/2

The electronic power supply versions can house both 26 W and 32 W compact fluorescent lamps with GX24q-3 coupling.

EMERGENCY VERSIONS

WIRED VERSIONS FOR FLUORESCENT LAMPS - IP55 - CLASS II

GW82246



Code	No. lamps	Lamp power	Lamp type	Lamp holder	Duration	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 220 / 240 V - 50 / 60 Hz								
GW 82 246	1	26 - 32 W	FSQ	GX24q-3	1 h	Graphite grey		1/2
GW 82 247	1	26 - 32 W	FSQ	GX24q-3	1 h	White		1/2

NEW

COMPLEMENTARY ITEMS FOR WALL INSTALLATION

GW82290



SWIVEL BRACKET

Code	Material	External Dim. LxHxD (mm)	Colour	Pack Carton
GW 82 290	Die-cast aluminium	140x120x100	Graphite grey	1/6
GW 82 255	Die-cast aluminium	140x120x100	White	1/6

APPLICATIONS: allows surface installation of the device and to adjust the vertical inclination by 45° upwards and 45° downwards with respect to the horizontal axis.

GW82291



ANGLE BRACKET

Code	Material	External Dim. LxHxD (mm)	Colour	Pack Carton
GW 82 291	Die-cast aluminium	90x80x100	Graphite grey	1/5
GW 82 253	Die-cast aluminium	90x80x100	White	1/5

APPLICATIONS: allows installation of the device on 90° corners.

NEW

COMPLEMENTARY ITEMS FOR INSTALLATION ON COLUMNS



GW82292

SINGLE LUMINAIRE SUPPORT COLUMN

Code	Material	Height (mm)	Recommended undergrounding	Colour	Pack Carton
GW 82 292	Aluminium extruded	1300	250 mm	Graphite grey	1
GW 82 259	Aluminium extruded	1300	250 mm	White	1
GW 82 293	Aluminium extruded	3000	500 mm	Graphite grey	1
GW 82 263	Aluminium extruded	3000	500 mm	White	1



GW82294

SUPPORT COLUMN FOR SINGLE DEVICE, COMPLETE WITH IP55 CONTAINER FOR 3 SYSTEM MODULES

Code	Material	Accessories supplied	Height (mm)	Recommended undergrounding	Colour	Pack Carton
GW 82 294	Aluminium extruded	3P Enclosure - black	1300	250 mm	Graphite grey	1
GW 82 273	Aluminium extruded	3P Enclosure - white	1300	250 mm	White	1



GW82295

DOUBLE LUMINAIRE SUPPORT COLUMN

Code	Material	Height (mm)	Recommended undergrounding	Colour	Pack Carton
GW 82 295	Aluminium extruded	1300	250 mm	Graphite grey	1
GW 82 261	Aluminium extruded	1300	250 mm	White	1
GW 82 296	Aluminium extruded	3000	500 mm	Graphite grey	1
GW 82 265	Aluminium extruded	3000	500 mm	White	1



GW82297

RECTANGULAR BASE FOR SUPPORT COLUMN OF MAX. HEIGHT 1300 MM

Code	Material	External Dim. LxHxD (mm)	Colour	Pack Carton
GW 82 297	Aluminium extruded	300x202x315	Graphite grey	1/4
GW 82 267	Die-cast aluminium	300x202x315	White	1/4

ACCESSORIES SUPPLIED: 2 M4 screws x 12 for fixing column to base.

CHARACTERISTICS: the fixing of the base + column to concrete is carried out with cramps sunk into it or via wall plugs with max screw Ø = 12 mm.

COMPLEMENTARY ITEMS FOR INSTALLATION ON POLE



GW82298

POLE MOUNTING SINGLE SWIVEL BRACKET Ø 60 MM

Code	Material	External Dim. LxHxD (mm)	Colour	Pack Carton
GW 82 298	Die-cast aluminium	160x140x100	Graphite grey	1/5
GW 82 257	Die-cast aluminium	160x140x100	White	1/5

APPLICATIONS: allows installation of the device on Ø 60 mm pole and to adjust the vertical inclination by 90° upwards and 45° downwards.



GW82299

POLE MOUNTING DOUBLE SWIVEL BRACKET Ø 60 MM

Code	Material	External Dim. LxHxD (mm)	Colour	Pack Carton
GW 82 299	Die-cast aluminium	160x140x100	Graphite grey	1/5
GW 82 270	Die-cast aluminium	160x140x100	White	1/5

APPLICATIONS: allows installation of the device on Ø 60 mm pole and to adjust the vertical inclination by 90° upwards and 45° downwards.

POLES



GW86775

CYLINDRICAL GALVANIZED STEEL POLES Ø 60 MM

Code	Length (mm)	Ø (mm)	Recommended undergrounding	Colour	Weight (Kg)	Pack Carton
GW 86 775	1000	60	200 mm	Graphite grey	3.5	1
GW 86 776	2000	60	300 mm	Graphite grey	7	1
GW 86 777	3000	60	500 mm	Graphite grey	10.5	1
GW 86 778	5000	60	500 mm	Graphite grey	14	1



GW86771

CYLINDRICAL FIBREGLASS POLES Ø 60 MM

Code	Length (mm)	Ø (mm)	Recommended undergrounding	Colour	Weight (Kg)	Pack Carton
GW 86 771	1000	60	200 mm	Smoke grey	0.7	1
GW 86 772	2000	60	300 mm	Smoke grey	1.5	1
GW 86 773	3000	60	400 mm	Smoke grey	2.2	1

APPLICATIONS: particularly suited for installation in marine environments or those particularly exposed to corrosive agents.



GW82289

ROUND BASE FOR FIXING STEEL POLES Ø 60 MM OF MAX. HEIGHT 2000 MM

Code	Material	Dimension (mm)	Colour	Pack Carton
GW 82 289	Steel	Ø 230 x h 350	Graphite grey	1/2

ACCESSORIES SUPPLIED: 2 M6 screws x 12 for fixing pole to base.

CHARACTERISTICS: the fixing of the base + column to concrete is carried out with cramps sunk into it or via wall plugs with max screw Ø = 12 mm.

COMPLEMENTARY ITEMS

SPARE PARTS

Code	Description	Dimension (mm)	Weight (Kg)	Pack Carton
GW 88 272	Tempered glass	280x250	0.6	1/5

NEW