



ASTRID 210 RANGE

PROFESSIONAL FLUSH-MOUNTING

GEWISS

IP20




STANDARD

WIRED VERSIONS FOR FLUORESCENT LAMPS - IP20 - CLASS II

GW82302



Ø 210



KCG EEI = B2



FSQ G24d-2



FSQ G24d-3

Code	No. lamps	Lamp power	Lamp type	Lamp holder	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 230 V - 50 Hz							
GW 82 301	1	18 W	FSQ	G24d-2	White	1.4	1
GW 82 302	2	18 W	FSQ	G24d-2	White	1.7	1
GW 82 303	1	26 W	FSQ	G24d-3	White	1.6	1
GW 82 304	2	26 W	FSQ	G24d-3	White	2.1	1
VOLTAGE: 240 V - 50 Hz							
GW 82 306	1	18 W	FSQ	G24d-2	White	1.4	1
GW 82 307	2	18 W	FSQ	G24d-2	White	1.7	1
GW 82 308	1	26 W	FSQ	G24d-3	White	1.6	1
GW 82 309	2	26 W	FSQ	G24d-3	White	2.1	1
VOLTAGE: 220 V - 60 Hz							
GW 82 311	1	18 W	FSQ	G24d-2	White	1.4	1
GW 82 312	2	18 W	FSQ	G24d-2	White	1.7	1
GW 82 313	1	26 W	FSQ	G24d-3	White	1.6	1
GW 82 314	2	26 W	FSQ	G24d-3	White	2.1	1

ELECTRONIC BALLAST

ASTRID 210 RANGE

GW82342



WIRED VERSIONS FOR FLUORESCENT LAMPS - IP20 - CLASS II



Ø 210



EVG EEI = A2



FSQ GX24q-2



FSQ GX24q-3

Code	No. lamps	Lamp power	Lamp type	Lamp holder	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 220 / 240 V - 50 / 60 Hz							
GW 82 341	1	18 W	FSQ	GX24q-2	White	1.1	1
GW 82 342	2	18 W	FSQ	GX24q-2	White	1.1	1
GW 82 343	1	26 - 32 W	FSQ	GX24q-3	White	1.2	1
GW 82 344	2	26 - 32 W	FSQ	GX24q-3	White	1.4	1

GW82343 and GW82344: the product can house both 26 W and 32 W compact fluorescent lamps with GX24q-3 coupling.

EMERGENCY VERSIONS

GW82348



WIRED VERSIONS FOR FLUORESCENT LAMPS - IP20 - CLASS II

Ø 210	EVG EEL= A2	EMERGENCY	FSQ GX24q-2	FSQ GX24q-3
-------	----------------	-----------	-------------	-------------

Code	No. lamps	Lamp power	Lamp type	Lamp holder	Duration	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 220 / 240 V - 50 / 60 Hz								
GW 82 347	1	18 W	FSQ	GX24q-2	1 h	White	1.8	1
GW 82 348	2	18 W	FSQ	GX24q-2	1 h	White	1.8	1
GW 82 349	1	26 - 32 W	FSQ	GX24q-3	1 h	White	1.8	1
GW 82 350	2	26 W	FSQ	GX24q-3	1 h	White	1.8	1
GW 82 371	2	32 W	FSQ	GX24q-3	1 h	White	1.8	1


IP44

STANDARD - WITH SCREEN

WIRED VERSIONS FOR FLUORESCENT LAMPS - IP44 - CLASS II



GW82321



Code	No. lamps	Lamp power	Lamp type	Lamp holder	Shield type	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 230 V - 50 Hz								
GW 82 321	1	18 W	FSQ	G24d-2	Acid-treated glass	White	1.6	1
GW 82 322	2	18 W	FSQ	G24d-2	Acid-treated glass	White	1.9	1
GW 82 323	1	26 W	FSQ	G24d-3	Acid-treated glass	White	1.8	1
GW 82 324	2	26 W	FSQ	G24d-3	Acid-treated glass	White	2.3	1
VOLTAGE: 240 V - 50 Hz								
GW 82 326	1	18 W	FSQ	G24d-2	Acid-treated glass	White	1.6	1
GW 82 327	2	18 W	FSQ	G24d-2	Acid-treated glass	White	1.9	1
GW 82 328	1	26 W	FSQ	G24d-3	Acid-treated glass	White	1.8	1
GW 82 329	2	26 W	FSQ	G24d-3	Acid-treated glass	White	2.3	1
VOLTAGE: 220 V - 60 Hz								
GW 82 331	1	18 W	FSQ	G24d-2	Acid-treated glass	White	1.6	1
GW 82 332	2	18 W	FSQ	G24d-2	Acid-treated glass	White	1.9	1
GW 82 333	1	26 W	FSQ	G24d-3	Acid-treated glass	White	1.8	1
GW 82 334	2	26 W	FSQ	G24d-3	Acid-treated glass	White	2.3	1

ELECTRONIC BALLAST - WITH SCREEN

WIRED VERSIONS FOR FLUORESCENT LAMPS - IP44 - CLASS II



GW82351



Code	No. lamps	Lamp power	Lamp type	Lamp holder	Shield type	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 220 / 240 V - 50 / 60 Hz								
GW 82 351	1	18 W	FSQ	GX24q-2	Acid-treated glass	White	1.3	1
GW 82 352	2	18 W	FSQ	GX24q-2	Acid-treated glass	White	1.3	1
GW 82 353	1	26 - 32 W	FSQ	GX24q-3	Acid-treated glass	White	1.4	1
GW 82 354	2	26 W	FSQ	GX24q-3	Acid-treated glass	White	1.6	1

GW82353: the product can house both 26 W and 32 W compact fluorescent lamps with GX24q-3 coupling.

EMERGENCY VERSION - WITH SCREEN

GW82357



WIRED VERSIONS FOR FLUORESCENT LAMPS - IP44 - CLASS II

--	--	--	--	--

Code	No. lamps	Lamp power	Lamp type	Lamp holder	Duration	Colour	Weight (Kg)	Pack Carton
VOLTAGE: 220 / 240 V - 50 / 60 Hz								
GW 82 357	1	18 W	FSQ	GX24q-2	1 h	White	1.7	1
GW 82 358	2	18 W	FSQ	GX24q-2	1 h	White	1.8	1
GW 82 359	1	26 - 32 W	FSQ	GX24q-3	1 h	White	1.8	1
GW 82 360	2	26 W	FSQ	GX24q-3	1 h	White	1.8	1

COMPLEMENTARY ITEMS

GW82361



SPARE PARTS

Code	Description	Material	Weight (Kg)	Pack Carton
GW 82 361	Glass	Tempered glass	0.2	1