

47 CVX 250 RANGE

SURFACE-MOUNTING DISTRIBUTION BOARDS UP TO 250A











SELECTION GUIDE

CVX 250 STRUCTURES

General characteristics In: up to 250A Capacity: 24* modules each row Installation: Interiors Colour: RAL 7035 grey	IP 40		IP 55		MAX. NO. ROWS/NO. MODULES	
						
FUNCTIONAL HEIGHT	Glass door		Glass door		Pitch 150 mm	Pitch 200 mm
1000	GW 47 015		GW 47 035		 6 rows - 144 modules*	 5 rows - 120 modules*
1200	GW 47 016		GW 47 036		 8 rows - 192 modules*	 6 rows - 144 modules*

*EN 50022 modules (17.5 mm)

47 CVX 250 RANGE

Board functional height (mm)	SPARE DOORS			
	IP 40		IP 55	
	Glass door	Solid door	Glass door	Solid door
1000	 GW 47 113	 GW 47 123	 GW 47 133	 GW 47 143
1200	 GW 47 114	 GW 47 124	 GW 47 134	 GW 47 144

47 CVX 250 RANGE

SURFACE-MOUNTING DISTRIBUTION BOARDS UP TO 250A



SELECTION GUIDE

CVX 250 BOARD CONFIGURATION

		H panel (mm)	B= 600 mm (24 mod.)
	Installation on DIN rail kit	150	GW 47 501
		200	GW 47 502
		300	GW 47 503
	Front panels with windows	150	GW 47 283
		200	GW 47 284
		300	GW 47 285
	Solid front panels	50	GW 47 511
		150	GW 47 512
		200	GW 47 513
		400	GW 47 514
		600	GW 47 515
	No. 2 Inst. 72x72 mm No. 2 Switches	200	GW 47 531
	No. 2 Inst. 96x96 mm No. 2 Switches	200	GW 47 532
	No. 4 Inst. 72x72 mm No. 1 Switch	200	GW 47 533
	No. 4 Inst. 96x96 mm No. 1 Switch	200	GW 47 534
	DIN 50022 {	-	GW 47 681
	DIN 50022 Twin - Aluminium }	-	GW 47 685
	DIN 50035 }	-	GW 47 682
	Back-mounting plates	200	GW 47 661
		400	GW 47 662
		600	GW 47 663

		FIXED EXECUTION			
		B= 600 mm (24 mod.)			
		Horizontal installation		Vertical installation	
MTS/MSS front junction kit	Poles No.	Code	H panel (mm)	Code	H panel (mm)
MTS 160	3P	GW 47 572	200	-	-
	4P	GW 47 573	200	-	-
MTS 160 with bottom-mounting residual current device (BDS 160)	4P	GW 47 582	200	-	-
MTS 250 MTSM 250	3-4P	GW 47 574	200	GW 47 561	400
MTS 250 with bottom-mounting residual current device (BDS 250)	4P	GW 47 584	300	-	-
MTS 250/ MTSM 250 on plate with DIN 50023 rail	3-4P	-	-	GW 47 551	300
MTSE 250		GW 47 575	200	GW 47 562	400
MSS 250		GW 47 591	300	GW 47 591	300

47 CVX 250 RANGE