








# 47 CVX 630 RANGE

FLOOR-MOUNTING DISTRIBUTION BOARDS UP TO 630A



## SELECTION GUIDE

### CVX 630 STRUCTURES

FUNCTIONAL DIM. (BxH)		600 x 1400 mm	600 x 1800 mm	850 x 1800 mm	
Modular capacity	Pitch 150mm	216 mod. (24x9)	288 mod. (24x12)	288 mod. (24x12)	432 mod. (36x12)
	Pitch 200 mm	168 mod. (24x7)	216 mod. (24x9)	216 mod. (24x9)	324 mod. (36x9)
Structures		GW 47 401	GW 47 402	GW 47 403	
Solid side panels		GW 47 411	GW 47 412	GW 47 412	
Aerated side panels		GW 47 421	GW 47 422	GW 47 422	
IP 30 Profiles		GW 47 431	GW 47 432	GW 47 433	
IP 55 Glass doors in curved glass		GW 47 451	GW 47 452	GW 47 453	
IP 55 Solid doors		GW 47 461	GW 47 462	GW 47 463	
Internal cable compartment		-	-	GW 47 471	

47 CVX 630 RANGE

# 47 CVX 630 RANGE

FLOOR-MOUNTING DISTRIBUTION BOARDS UP TO 630A



## SELECTION GUIDE

### CVX 630 DISTRIBUTION BOARD CONFIGURATION

		Panel height (mm)	B= 600 mm (24 mod.)	B= 850 mm (36 mod.)
	DIN rail Installation kit	150	GW 47 501	GW 47 506
		200	GW 47 502	GW 47 507
		300	GW 47 503	GW 47 508
	Front panels with windows	150	GW 47 283	GW 47 286
		200	GW 47 284	GW 47 287
		300	GW 47 285	GW 47 288
	Solid front panels	50	GW 47 511	GW 47 521
		150	GW 47 512	GW 47 522
		200	GW 47 513	GW 47 523
		400	GW 47 514	GW 47 524
		600	GW 47 515	GW 47 525
	Solid front panels	No. 2 72x72 mm instrum. No. 2 switches	GW 47 531	GW 47 536
		No. 2 96x96 mm instrum. No. 2 switches	GW 47 532	GW 47 537
		No. 4 72x72 mm instrum. No. 1 switch	GW 47 533	GW 47 538
		No. 4 96x96 mm instrum. No. 1 switch	GW 47 534	GW 47 539
	Aerated panels	200	GW 47 541	GW 47 542
	DIN rails	DIN 50022	GW 47 681	GW 47 683
		DIN 50022 twin - aluminium	GW 47 685	GW 47 686
		DIN 50035	GW 47 682	GW 47 684
	Back-mounting plates	200	GW 47 661	GW 47 666
		400	GW 47 662	GW 47 667
		600	GW 47 663	GW 47 668

		FIXED EXECUTION							
		B= 600 mm (24 mod.)				B= 850 mm (36 mod.)			
		Horizontal installation		Vertical installation		Horizontal installation		Vertical installation	
MTS/MSS front coupling kit	No. poles	Code	Panel height (mm)	Code	Panel height (mm)	Code	Panel height (mm)	Code	Panel height (mm)
MTS 160	3P	GW 47 572	200	-	-	-	-	-	-
	4P	GW 47 573	200	-	-	-	-	-	-
MTS 160 with residual current device (BDS 160)	4P	GW 47 582	200	-	-	GW 47 583	200	-	-
MTS 250 / MTSM 250	3-4P	GW 47 574	200	GW 47 561	400	GW 47 577	200	-	-
MTS 250 with residual current device (BDS 250)	4P	GW 47 584	300	-	-	GW 47 585	300	-	-
MTS 250 / MTSM 250 on plate with 50023 DIN rail	3-4P	-	-	GW 47 551	300	-	-	GW 47 552	300
MTSE 250		GW 47 575	200	GW 47 562	400	GW 47 578	200	-	-
MTS 630 / MTSE 630		GW 47 576	300	GW 47 563	500	GW 47 579	300	-	-
MSS 250		GW 47 591	300	GW 47 591	300	GW 47 594	300	GW 47 594	300
MSS 630		GW 47 592	400	GW 47 593	500	GW 47 595	400	GW 47 596	500

47 CVX 630 RANGE