

40 CDI RANGE

FLUSH-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



SELECTION GUIDE

40 CDI RANGE

40 CDK RANGE - FLUSH-MOUNTING PROTECTED ENCLOSURES AND DISTRIBUTION BOARDS

ENCLOSURES

Protection rating: IP 40
Colour: RAL 9016 white
Door: smoked transparent
 transparent



COMPLEMENTARY ITEMS	No. modules	2	4	6	8	12	18	24 (12x2)
	Door Smoked	GW 40 601	GW 40 602	GW 40 603	GW 40 604	GW 40 605	GW 40 608	GW 40 606
Door Blank		GW 40 882	GW 40 883	GW 40 884	GW 40 885	GW 40 888	GW 40 886	
INSTALLATION AND JOINTING								
 Anti-deformation brackets for walling enclosure base boxes	-	-	-	-	-	-	-	-
 Combined coupling component	-	-	-	-	GW 40 425	GW 40 425	GW 40 425	
 Kit of 4 long screws with spacers	-	-	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	
WIRING								
 Insulated neutral and earth terminal blocks	-	-	-	GW 40 401	GW 40 402	GW 40 404	GW 40 402	
 Internal horizontal dividers	-	-	-	-	-	-	GW 40 487	
 1-module high blank cover panels for CDK boards	-	-	-	-	-	-	2x GW 40 495	
MISCELLANEOUS								
 Metal cylinder security lock	GW 40 422	GW 40 422	GW 40 422	GW 40 422	GW 40 422	GW 40 422	GW 40 422	
 Triangular key	-	-	-	-	-	-	-	

40 CDI RANGE

FLUSH-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



SELECTION GUIDE

40 CDI RANGE

40 CD RANGE - FLUSH-MOUNTING PROTECTED ENCLOSURES

DISTRIBUTION BOARDS			ARRANGED FOR TERMINAL BLOCK HOUSING				EQUIPPED WITH TERMINAL BLOCKS		
Protection class: IP 40 Colour: RAL 9016 white Door: smoked transparent transparent			Protection rating: IP 40 Colour: RAL 9016 white Door: transparent				Protection rating: IP 40 Colour: RAL 9016 White Door: transparent		
36 (18x2)	54 (18x3)	72 (18x4)	8	12+1	24+2 (12x2)	36+2 (18x2)	12+1	24+2 (12x2)	36+2 (18x2)
GW 40 609	GW 40 610	GW 40 611							
GW 40 889	GW 40 890	GW 40 891	GW 40 655	GW 40 657	GW 40 659	GW 40 661	GW 40656	GW 40 658	GW 40 660
GW 40 479	GW 40 479	2x GW 40 479	-	-	-	-	-	-	-
GW 40 425	GW 40 425	GW 40 425	-	-	-	-	-	-	-
GW 48 645	GW 48 645	2x GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645
2x GW 40 404	2x GW 40 404	2x GW 40 404	GW 40 401	GW 40 402	2x GW 40 401	2x GW 40 402	supplied	supplied	supplied
GW 40 488	2x GW 40 488	3x GW 40 488	-	-	-	-	-	-	-
2x GW 40 496	3x GW 40 496	4x GW 40 496	-	-	-	-	-	-	-
GW 40 422	2x GW 40 422	2x GW 40 422	-	-	-	-	-	-	-
-	-	-	-	GW 40 421	GW 40 421	GW 40 421	GW 40 421	GW 40 421	GW 40 421

40 CDI RANGE

FLUSH-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



SELECTION GUIDE

40 CDI RANGE

40 CD RANGE - FLUSH-MOUNTING DECORATIVE PROTECTED ENCLOSURES









ARRANGED FOR TERMINAL BLOCK HOUSING

EQUIPPED WITH TERMINAL BLOCKS

Protection rating: IP 40
 Colour: RAL 9016 white - Toner black
 Door: smoked transparent
 Frame: White
 Black

Protection rating: IP 40
 Colour: RAL 9016 white - Toner black
 Door: smoked transparent
 Frame: White
 Black



COMPLEMENTARY ITEMS	No. modules	4	8	12	24 (12x2)	36 (12x3)	12	24 (12x2)	36 (12x3)
	Frame white	GW 40 237	GW 40 225	GW 40 229	GW 40 233	GW 40 239	GW 40 227	GW 40 231	GW 40 241
	Frame black	GW 40 238	GW 40 226	GW 40 230	GW 40 234	GW 40 240	GW 40 228	GW 40 232	GW 40 242
INSTALLATION AND JOINTING									
 Kit for sealing fronts	-	-	-	-	-	-	-	-	-
 Coupling component	-	-	-	-	-	-	-	-	-
 Kit of 4 long screws with spacers	-	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645
WIRING									
 Insulated neutral and earth terminal blocks	-	GW 40 401	GW 40 402	2x GW 40 401	2x GW 40 402	supplied	supplied	supplied	supplied
 Internal horizontal dividers	-	-	-	-	-	-	-	-	-
 Internal vertical separators	-	-	-	-	-	-	-	-	-
MISCELLANEOUS									
 SECURITY LOCK	-	-	-	-	-	-	-	-	-
 Metal cylinder security lock for 48PTC	-	-	-	-	-	-	-	-	-

40 CDI RANGE

FLUSH-MOUNTING DISTRIBUTION BOARDS AND ENCLOSURES



SELECTION GUIDE

40 CDI RANGE

40 CD RANGE - CO-ORDINATED ENCLOSURES WITH AUTOMATIC OPENING		48 PTC RANGE - WATERTIGHT MODULAR ENCLOSURES			40 CD RANGE - ENCLOSURES FOR PLASTERBOARD WALLS			
DOOR WITH AUTOMATIC OPENING		MODULAR ENCLOSURES		COMBINED BOARDS	BLANK DOOR			
Protection rating: IP 40 Colour: 14 versions co-ordinated with GEWISS plaques Door with automatic opening <i>See technical-commercial tables for code detail</i>		Protection rating: IP 55 Colour: RAL 7035 grey Door: smoked transparent		Protection rating: IP 55 Colour: RAL 7035 grey Door: smoked transparent	Protection rating: IP 30 Colour: RAL 9016 white Door: transparent Frame: metal			
12	24	6	12	4	12+2	24+4 (12x2)	36+6 (12x3)	48+8 (12x4)
		GW 48 681	GW 48 682	GW 48 686	GW 40 161	GW 40 162	GW 40 163	GW 40 164
-	-	GW 48 643	GW 48 643	GW 48 643	-	-	-	-
-	-	GW 48 026	GW 48 026	GW 48 026	-	-	-	-
GW 48 645	GW 48 645	GW 48 645	GW 48 645	GW 48 645	-	-	-	-
GW 40 402	2x GW 40 402	-	-	-	supplied	supplied	supplied	supplied
-	-	-	-	-	GW 40 460	GW 40 460	GW 40 460	GW 40 460
-	-	-	-	-	GW 40 456	GW 40 457	GW 40 458	GW 40 459
-	-	-	-	-	GW 40 463	GW 40 463	GW 40 463	GW 40 463
-	-	GW 48 644	GW 48 644	GW 48 644	-	-	-	-