

44 CE RANGE

WATERTIGHT SURFACE-MOUNTING JUNCTION BOXES



SELECTION GUIDE

44 CE RANGE - SURFACE-MOUNTING JUNCTION BOXES

Heat resistance		GW PLAST 75 (TP 85°C)					GW PLAST 120 (TP 120°C)	
Fire resistance		GWT 650°C - UL 94 : HB <input type="checkbox"/> GWT 960°C - UL 94 : VO <input type="checkbox"/>					GWT 650° C - UL 94 : HB <input type="checkbox"/>	
Characteristics		IP 44 with cable entries	IP 55 1/4 turn with cable entries	IP 55 1/4 turn with smooth walls	IP 55 with cable entries	IP 56 with smooth walls	IP 56 smooth walls blank cover	IP 56 smooth walls transparent cover
Dimensions (mm)	Cover							
Ø 65	shallow	GW 44 001						
		GW 44 051						
Ø 80	shallow	GW 44 002						
		GW 44 052						
80 x 80	shallow	GW 44 003						
		GW 44 053						
100 x 100	shallow		GW 44 024	GW 44 234	GW 44 004	GW 44 204	GW 44 404	
		GW 44 054			GW 44 274			
	deep					GW 44 214	GW 44 414	
120 x 80	shallow				GW 44 005	GW 44 205	GW 44 405	
					GW 44 055	GW 44 275		
	deep					GW 44 215	GW 44 415	
150 x 110	shallow		GW 44 026	GW 44 236	GW 44 006	GW 44 206	GW 44 406	GW 44 426
		GW 44 056			GW 44 276			
	deep					GW 44 216	GW 44 416	GW 44 436
190 x 140	shallow				GW 44 007	GW 44 207	GW 44 407	GW 44 427
					GW 44 057	GW 44 277		
	deep					GW 44 217	GW 44 417	GW 44 437
240 x 190	shallow				GW 44 008	GW 44 208	GW 44 408	GW 44 428
					GW 44 058	GW 44 278		
	deep					GW 44 218	GW 44 418	GW 44 438
300 x 220	shallow				GW 44 009	GW 44 209	GW 44 409	GW 44 429
					GW 44 059	GW 44 279		
	deep					GW 44 219	GW 44 419	GW 44 439
380 x 300	shallow				GW 44 010	GW 44 210	GW 44 410	GW 44 430
					GW 44 060	GW 44 280		
	deep					GW 44 220	GW 44 420	GW 44 440
460 x 380	shallow				GW 44 011	GW 44 211	GW 44 411	GW 44 431
					GW 44 061	GW 44 281		
	deep					GW 44 221	GW 44 421	GW 44 441

LEGEND: GWT 650°C - UL94 : HB
 GWT 960°C - UL94 : VO
IN BOLD : versions with halogen-free material

44 CE RANGE








BOX BASE DIMENSIONS

44 CE RANGE

WATERTIGHT SURFACE-MOUNTING JUNCTION BOXES



SELECTION GUIDE

		ACCESSORIES APPLICATION TABLE											
		BASE DIMENSIONS OF BOX (mm)											
		Code	Ø 65	Ø 80	80 x 80	100 x 100	120 x 80	150 x 110	190 x 140	240 x 190	300 x 220	380 x 300	460 x 380
ACCESSORIES FOR COUPLING AND JUNCTION SURFACE-MOUNTING BOXES	EQUIPOTENTIAL SINGLE-POLE TERMINAL BLOCKS	 GW 44 671	●	●	●	●	●	●	●	●	●	●	●
		GW 44 672		●	●	●	●	●	●	●	●	●	●
		GW 44 673 GW 44 674				●		●	●	●	●	●	●
		GW 44 675						●	●	●	●	●	●
		GW 44 676						●	●	●	●	●	●
	MULTIPLE TERMINAL BLOCKS	 GW 44 606	●	●	●	●	●						
		GW 44 607	●	●	●	●	●						
		GW 44 608	●	●	●	●	●						
	MULTIPLE FEEDTHROUGH TERMINAL BLOCKS	 GW 44 609 GW 44 610		●	●	●	●	●	●	●	●	●	●
		GW 44 611 GW 44 612				●	●	●	●	●	●	●	●
		GW 44 613 GW 44 614							●	●	●	●	●
	BACK-MOUNTING PLATES	Metal	 GW 44 615							●			
			GW 44 616							●			
			GW 44 617								●		
			GW 44 618									●	
			GW 44 619										●
		Insulating	 GW 44 625							●			
			GW 44 626								●		
			GW 44 627									●	
GW 44 628												●	
GW 44 628												●	
RACC.	 GW 44 620									●	●	●	
SCREW CAPS	 GW 44 622	2	2	2	4	4	4	4	4	4			
	GW 44 623										6	supplied	
BRACKET	 GW 44 621							6	8	12	16	8	

44 CE RANGE