

SELECTION GUIDE

COUPLINGS FOR RIGID CONDUIT/CABLE ENDS AND BOX ENDS													
Assembly hole Ø (mm)	Cable glands							Conduit/box couplings				Cable entries	
	IP66 - PG pitch		IP68 - ISO pitch		IP66 - PG pitch With housing for rigid conduit			IP66		IP44		IP55	
	Code	for cables Ø (mm)	Code	for cables Ø (mm)	Code	for cables Ø (mm)	for conduits Ø (mm)	Code	for conduits Ø (mm)	Code	for conduits Ø (mm)	Code	for conduits and cables Ø (mm)
12			GW 52 042	3 ÷ 6.5									
12.5	GW 52 001	3 ÷ 6											
16	GW 52 002	5 ÷ 8	GW 52 043	5 ÷ 10									
19	GW 52 003	7 ÷ 10.5											
20	GW 52 004	9 ÷ 12.5	GW 52 044	10 ÷ 14	GW 52 024	9 ÷ 12.5	16	GW 50 415	16			GW 50 428	16
23	GW 52 005	13 ÷ 16			GW 52 025	13 ÷ 16	20	GW 50 416	20	GW 50 421	16	GW 50 429	20
25			GW 52 045	13 ÷ 18						GW 50 422	20		
29	GW 52 006	8 ÷ 10 17 ÷ 20			GW 52 026	8 ÷ 10 17 ÷ 20	25	GW 50 417	25	GW 50 423	20	GW 50 430	25
32			GW 52 046	18 ÷ 25						GW 50 424	25		
37	GW 52 007	13.5 ÷ 15 21 ÷ 26			GW 52 027	13.5 ÷ 15 21 ÷ 26	32	GW 50 418	32	GW 50 425	32	GW 50 431	32
40			GW 52 047	22 ÷ 32						GW 50 426	40		
48	GW 52 008	17 ÷ 20 30 ÷ 34			GW 52 028	17 ÷ 20 30 ÷ 34	40	GW 50 419	40	GW 50 427	50	GW 50 432	40
50			GW 52 048	30 ÷ 38									
54	GW 52 009	36 ÷ 39 40 ÷ 43			GW 52 029	36 ÷ 39 40 ÷ 43	50	GW 50 420	50				
60	GW 52 010	38 ÷ 40 46 ÷ 50											
63			GW 52 049	35 ÷ 44									

FIXING COMPONENTS

Snap-on supports 50 AC range	Saddle snap clips 50 AC range	Rail for 50 AC range supports	Clips with pins		M6 thread steel collars - 2 screws		Steel clips 14x6 hole	Steel U-bolt with two holes	Fixing collar		Fixing dowels		
			internal section	internal section	Reopenable CFR	Not reopenable CF			For 6 mm section holes	For 8 mm section holes			
GW 50 601	GW 50 605	GW 50 609	15-16	GW 50 616	16-17	GW 50 804	GW 50 814	GW 50 824	DX 51 120	DX 51 232		DX 51 306	DX 51 308
GW 50 602	GW 50 606	GW 50 609	19-20	GW 50 617	19-20	GW 50 805	GW 50 815	GW 50 825	DX 51 120	DX 51 232		DX 51 306	DX 51 308
			21-22	GW 50 618	21-22	GW 50 806	GW 50 816	GW 50 826					
GW 50 603	GW 50 607	GW 50 609	25-26	GW 50 619	25-26	GW 50 807	GW 50 817	GW 50 827		DX 51 232	DX 51 263	DX 51 306	DX 51 308
GW 50 604	GW 50 608	GW 50 609	31-32	GW 50 620	31-32	GW 50 808	GW 50 818	GW 50 828		DX 51 232	DX 51 263	DX 51 306	DX 51 308
GW 50 628	GW 50 630	GW 50 609			38-40	GW 50 809	GW 50 819	GW 50 829			DX 51 263	DX 51 306	DX 51 308
GW 50 629	GW 50 631	GW 50 609			48-50	GW 50 810	GW 50 820	GW 50 830			DX 51 263	DX 51 306	DX 51 308
											DX 51 263	DX 51 306	DX 51 308

TRUNKING END COUPLINGS

Assembly hole Ø (mm)	Distance of the centre of the assembly hole from the wall (mm)	Trunking couplings - IP 40													
		For trunking sizes (mm)													
		Codes	15 x 15	15 x 17	22 x 10	25 x 17	25 x 25	30 x 15	30 x 30	40 x 17	40 x 25	40 x 30	40 x 40		
23	17	GW 50 441													
23	20	GW 50 442													
29	23	GW 50 443			22 x 10	25 x 17	25 x 25	25 x 30	30 x 15	30 x 25	30 x 30	40 x 17	40 x 25	40 x 30	40 x 40
37	29	GW 50 445													

Couplings have reference markings on the inside so that they can be coupled with all the trunking shown in the table.