

SELECTION GUIDE

Ø SHEATH	SPIRALLED SHEATHS					ROTATING STRAIGHT PIPE FITTINGS - RD IP 64 RANGE					
	DIFLEX range				LIGHT range	RDM			RDG		
	Grey with cable puller	Grey	Black	Blue	Grey	ISO pitch	Grey	Black	GAS pitch	Grey	Black
8											
10		DX 30 010	DX 30 110	DX 30 210		M12x1.5	DX 54 010	DX 54 110	1/4"	DX 54 210	DX 54 310
12	DX 30 312	DX 30 012	DX 30 112	DX 30 212	DX 30 812	M16x1.5	DX 54 012	DX 54 112	3/8"	DX 54 212	DX 54 312
14		DX 30 014	DX 30 114	DX 30 214					1/2"	DX 54 214	DX 54 314
16	DX 30 316	DX 30 016	DX 30 116	DX 30 216	DX 30 816	M20x1.5	DX 54 016	DX 54 116	1/2"	DX 54 216	DX 54 316
20	DX 30 320	DX 30 020	DX 30 120	DX 30 220	DX 30 820	M25x1.5	DX 54 020	DX 54 120	3/4"	DX 54 220	DX 54 320
22		DX 30 022	DX 30 122	DX 30 222		M25x1.5	DX 54 022	DX 54 122	3/4"	DX 54 222	DX 54 322
25	DX 30 325	DX 30 025	DX 30 125	DX 30 225	DX 30 825	M32x1.5	DX 54 025	DX 54 125	1"	DX 54 225	DX 54 325
28		DX 30 028	DX 30 128	DX 30 228		M32x1.5	DX 54 028	DX 54 128	1"	DX 54 228	DX 54 328
32		DX 30 032	DX 30 132	DX 30 232		M40x1.5	DX 54 032	DX 54 132	1 1/4"	DX 54 232	DX 54 332
35		DX 30 035	DX 30 135	DX 30 235					1 1/4"	DX 54 235	DX 54 335
40		DX 30 040	DX 30 140	DX 30 240		M50x1.5	DX 54 040	DX 54 140	1 1/2"	DX 54 240	DX 54 340
50		DX 30 050	DX 30 150	DX 30 250		M63x1.5	DX 54 050	DX 54 150	2"	DX 54 250	DX 54 350
60		DX 30 060	DX 30 160	DX 30 260							

Ø SHEATH	ROTATING CURVED PIPE FITTINGS RC IP64 RANGE						IP65 PIPE FITTINGS						
	RCG		RCPG				RMG conduit-sheath pipe fitting		New RMG/N new conduit-sheath pipe fitting		MDG-G sheath-sheath coupling	RGC sheath-cable union	
	GAS pitch	Grey	Black	PG pitch	Grey	Black	Ø conduit		Ø conduit			Ø cable	
8													
10	1/4"	DX 55 010	DX 55 110	9	DX 55 210	DX 55 310							
12	3/8"	DX 55 012	DX 55 112	11 13.5	DX 55 212 DX 55 213	DX 55 312 DX 55 313	16	DX 43 316			DX 55 812		
14													
16	1/2"	DX 55 016	DX 55 116	13.5 16	DX 55 216 DX 55 217	DX 55 316 DX 55 317	20	DX 43 320	16	DX 43 416	DX 55 816	3-6 6-9 9-12	DX 55 613 DX 55 616 DX 55 619
20	3/4"	DX 55 020	DX 55 120	21	DX 55 220	DX 55 320	25	DX 43 325	20	DX 43 420	DX 55 820	3-6 6-9 9-12	DX 55 623 DX 55 626 DX 55 629
22													
25	1"	DX 55 025	DX 55 125	29	DX 55 225	DX 55 325	32	DX 43 332	25	DX 43 425			
28									32	DX 43 432			
32	1 1/4"	DX 55 032	DX 55 132	36	DX 55 232	DX 55 332	40	DX 43 340					
35													
40							50	DX 43 350	40	DX 43 440			









DF RANGE

DF RANGE

FLEXIBLE PROTECTIVE CONDUIT SYSTEMS



SELECTION GUIDE

ROTATING STRAIGHT PIPE FITTINGS - RD IP 64 RANGE			FIXED STRAIGHT PIPE FITTINGS- RUN IP 64 RANGE									
RDPG			RUN-M			RUN-G			RUN-PG			
PG pitch	Grey	Black	ISO pitch	Grey	Black	GAS pitch	Grey	Black	PG pitch	Grey	Black	
7												
7	DX 54 408	DX 54 508	M12x1	DX 56 008	DX 56 108	1/4"	DX 56 208	DX 56 308	7	DX 56 408	DX 56 508	
7	DX 54 410	DX 54 510	M16x1.5	DX 56 010	DX 56 110	1/4"	DX 56 210	DX 56 310	7	DX 56 410	DX 56 510	
9	DX 54 411	DX 54 511							9	DX 56 411	DX 56 511	
11	DX 54 412	DX 54 512	M16x1.5	DX 56 012	DX 56 112	3/8"	DX 56 212	DX 56 312	11	DX 56 412	DX 56 512	
13.5	DX 54 413	DX 54 513							13.5	DX 56 413	DX 56 513	
13.5	DX 54 414	DX 54 514	M16x1.5	DX 56 014	DX 56 114	1/2"	DX 56 214	DX 56 314	13.5	DX 56 414	DX 56 514	
13.5	DX 54 416 DX 54 417	DX 54 516 DX 54 517	M20x1.5	DX 56 016	DX 56 116	1/2"	DX 56 216	DX 56 316	11	DX 56 415	DX 56 515	
16									13.5	DX 56 416	DX 56 516	
16									16	DX 56 417	DX 56 517	
21	DX 54 420	DX 54 520	M25x1.5	DX 56 022	DX 56 122	3/4"	DX 56 222	DX 56 322	16	DX 56 422	DX 56 522	
21	DX 54 422	DX 54 522	M25x1.5	DX 56 022	DX 56 122	3/4"	DX 56 222	DX 56 322	21	DX 56 423	DX 56 523	
29	DX 54 425	DX 54 525	M25x1.5	DX 56 025	DX 56 125	3/4"	DX 56 225	DX 56 325	16	DX 56 422	DX 56 522	
29	DX 54 428	DX 54 528	M32x1.5	DX 56 028	DX 56 128	1"	DX 56 228	DX 56 328	21	DX 56 423	DX 56 523	
36	DX 54 432	DX 54 532				1 1/4"	DX 56 232	DX 56 332	21	DX 56 425	DX 56 525	
36	DX 54 435	DX 54 535				1 1/4"	DX 56 235	DX 56 335	36	DX 56 428	DX 56 528	
			M40x1.5	DX 56 040	DX 56 140	1 1/2"	DX 56 240	DX 56 340	36	DX 56 432	DX 56 532	
			M50x1.5	DX 56 050	DX 56 150	2"	DX 56 250	DX 56 350	42	DX 56 435	DX 56 535	
									48	DX 56 440	DX 56 540	
										48	DX 56 450	DX 56 550