

### Floodlight luminaire 230 V

Shape and Type of lamp		Fluorescent (W)							Halogen (W)			Discharge lamps							
												35W	70W						
	ME ellipse metal halides																		
	MT tubular metal halides												35	70					
	MD double connection metal halides														70				
	MN metal halides with cable																		
	SE ellipse high pressure sodium															70			
	ST tubular high pressure sodium																70		
	SD double connection high pressure sodium																70		
	QE mercury vapour																		
	Fluorescent	2x18	4x18	1x32	2x32	1x42	2x42	1x120W 3000°k	1x120W 4000°k										
	HS double-spined halogen									50	75	100							
	HD double connection halogen											500	1000	1500					
<b>Symmetrical optics</b>	<b>Genius</b> 	Graphite grey																	
		White																	
		Graphite grey infrared sensors																	
		White infrared sensors																	
		On the graphite grey tubular support																	
		On the white tubular support																	
<b>Asymmetrical optics</b>	<b>Mercurio</b> 	Graphite grey																	
		Aluminium																	
		Horus 1 diffused optics	GW 85 306		GW 85 367		GW 85 366												
		Horus 2 diffused optics		GW 85 016		GW 85 067		GW 85 066											
		Horus 3 diffused optics							GW 85 109F	GW 85 110F									
		Horus 3 restricted beam optics																	
<b>Circular beam</b>	<b>Mercurio</b> 	Graphite grey																	
		Aluminium																	
		Urano graphite grey																	
		Urano aluminium																	
		Urano white																	
		Horus 1 diffused optics																	
<b>Special optics</b>	<b>Colosseum</b> 	Horus 2 diffused optics																	
		Horus 3 diffused optics																	
		Horus 3 restricted beam optics																	
		Titano diffused optics																	
		Titano restricted beam optics																	
		Colosseum diffused optics																	
<b>Special optics</b>	<b>Colosseum</b> 	Colosseum restricted beam optics																	
		Adjustable beam 6°-30°																	
		Graphite grey																	
		Aluminium																	
		Circular optics 8°																	
		Restricted beam optics 8°																	
<b>Special optics</b>	<b>Colosseum</b> 	Semi restricted beam optics 25°																	
		Diffused optics 40°																	
		Hot restrike restricted beam optics 8°																	
		Hot-restrike semi restricted beam optics 25°																	
		Hot-restrike diffused optics 40°																	

\* Lamp with 0.7 ÷ 1 kV striking voltage.

